



POLARIS®
PRO XD FULL-SIZE GAS CREW



KAWASAKI®
MULE® PRO-FXT EPS



JOHN DEERE®
XUV825M S4



CLUB CAR®
CARRYALL® 1700 4WD

SAFETY

SAFETY IS NUMBER ONE FOR COMMERCIAL AND GOVERNMENT USERS, AND IMPORTANT TO CONSIDER WHEN PURCHASING A FLEET. SEE HOW THESE VEHICLES STACK UP TO KEEP YOUR EMPLOYEES SAFE.

Standard Safety Features

A horn and backup alarm are not always a stock product, but enhances safety on the job site.

Horn, Backup Alarm

Horn, Backup Alarm (opt)

Horn

Backup Alarm

Lighting

Proper headlights and taillights provide improved visibility.

Hi/Low 55W/60W Halogen Headlights, LED Tail/Brake Lights

Halogen Headlights , LED Subheadlights, 55W Tail/Brake Lights

Single-beam 50W Halogen with Tailights

55W Halogen Headlight, Taillight (opt)

Body Colors

Orange decals provide increased pedestrian visibility.

Gray with Orange Graphics

Timberline Green, Bright White

Green/Yellow, Camouflage, Olive/Black

Dark Gray, Dark Green

Seatbelts

More points on the seatbelt make the passenger more secure. Orange seatbelts improve visibility to ensure operators are wearing them at all times.

Orange, 3-point

Black, 3-point

Black, 3-point

Black, 2-point

Top Speed

Speed is often limited to meet jobsite requirements.

40 mph (64 kph) (26 mph/42 kph from factory) with limiting options down to 15 mph (24 kph)

45 mph (72 kph)

44 mph (70 kph)

25 mph (40 kph)

OPEI Certification

OPEI Certification involves approved safety features including an occupant protective structure (OPS).

Yes

N/A

N/A

N/A

DURABILITY

DURABILITY IS KEY TO HELP PREVENT VEHICLE BREAKDOWNS AND TIME CONSUMING MAINTENANCE. SEE HOW THESE VEHICLES HAVE BEEN DURABLY ENGINEERED TO KEEP RUNNING LONGER.

Engine

Polaris®
ProStar 1,000cc 4-cycle Gas

812cc 4-stroke 3 Cylinder

Kawasaki®
812cc 4-cylinder

Kawasaki®
675cc 4-cycle 2 Cylinder

Bed Box Dimensions

A larger box bed will allow for hauling more or heavier goods.

43.5 x 54 x 11.5 in
(110.5 x 137 x 29 cm)

42.7 x 53.7 x 11 in (3-person)
(108.5 x 136.4 x 27.9 cm 3-person)
22 x 53.7 x 11 in (6-person)
(55.9 x 136.4 x 27.9 cm 6-person)

45 x 52 x 12 in
(114.3 x 132 x 30.5 cm)

48.8 x 49.8 x 10.9 in
(123 x 128 x 28 cm)

Box Cargo Capacity

More cargo capacity will allow for hauling larger loads, but not necessarily heavier loads.

1,250 lb (567 kg)

350 lb (158 kg) (6-person)

1,000 lb (454 kg)

800 lb (363 kg)

Box Bed Material

Heavy-duty poly will help reduce damage and rust to the box, reducing maintenance.

Heavy-duty Poly

Steel

Heavy-duty Poly

Aluminum,
Powder-coated Steel (opt)

Towing Capacity

Having a high towing capacity allows you to trailer more goods and reduce trips on the jobsite.

2,500 lb (1134 kg)

2,000 lb (907.2 kg)

1,500 lb (680 kg)

2,000 lb (907.2 kg)



POLARIS®
PRO XD FULL-SIZE GAS CREW



KAWASAKI®
MULE® PRO-FXT EPS



JOHN DEERE®
XUV825M S4



CLUB CAR®
CARRYALL® 1700 4WD

DURABILITY (CONT.)

DURABILITY IS KEY TO HELP PREVENT VEHICLE BREAKDOWNS AND TIME CONSUMING MAINTENANCE. SEE HOW THESE VEHICLES HAVE BEEN DURABLY ENGINEERED TO KEEP RUNNING LONGER.

Payload Capacity

Having more payload will allow you to haul more goods and people.

2,075 lb (941 kg)

1,616 lb (733 kg)

1,400 lb (635 kg)

1,600 lb (817 kg)

Drive System Type

Auto engagement into all wheel drive helps when the rear tires slip, preventing getting stuck in problematic terrain. Turf mode allows for minimal impact on delicate terrain.

Selectable
Turf/2WD/4WD

Selectable 2WD/ 4WD

Selectable 2WD/4WD with
Differential Locks

IntelliTrak™ Automatic 4WD

Fuel Capacity

More fuel allows you to work longer on one tank.

11.5 gal (43.5 L)

7.9 gal (29.9L)

7.3 gal (27.6 L)

6.5 gal (24.6 L)

Ground Clearance

More ground clearance helps clear more uneven terrain without bottoming out.

11 in (27.9 cm)

10.2 in (25.9 cm)

11 in (27.9 cm)

8.2 in (21 cm)

Seat Covering

Stronger materials, like Kevlar®, are more damage, puncture, and wear resistant.

Kevlar®-Reinforced Vinyl

Vinyl

Vinyl

Vinyl

Driveline

A driveline built with quality, durable parts will last longer in rugged environments and lead less to vehicle downtime.

Heavy-duty Drive Shaft,
CVT Boots and Wheel Bearings

UTV standard Drive Shaft,
CVT Boots and Wheel Bearings

UTV standard Drive Shaft,
CVT Boots and Wheel Bearings

UTV standard Drive Shaft,
CVT Boots and Wheel Bearings

Tires

Thicker walls (ply) help prevent flat tires. A square-profiled tire provides more even tread wear on hard-packed surfaces, and 4 common-size tires make replacing quick and simple.

F: 8-ply 26 x 10-12
Duro Power Grip, Flat Profile
R: 8-ply 26 x 10-12
Duro Power Grip, Flat Profile

F: 4-ply 26 x 9-12,
All-Terrain
R: 4-ply 26 x 11-12,
All-Terrain

F: 27 x 9-14, Maxxis 2.0
Extreme Terrain Radials on
Steel or Alloy Wheels
R: 27 x 11-14, Maxxis Big-Horn
Extreme Terrain Radials on
Steel or Alloy Wheels

F: 4-ply 25 x 10.5-12,
All-Terrain
R: 4-ply 25 x 10.5-12,
All-Terrain

SERVICEABILITY

DOWNTIME KILLS PRODUCTIVITY. SEE HOW THESE VEHICLES HAVE BEEN ENGINEERED TO BE SERVICED BACK TO PEAK CONDITION WITH EASE.

Maintenance Interval (hours)

The longer the maintenance interval, the less downtime your vehicle will need for repairs.

100

100

100

100

Warning Alarms

More fault alarms notify the operator of potential issues that could cause serious damage to the vehicle.

Coolant Temperature Gauge,
Engine Oil Pressure Indicator,
Seatbelt Indicator, Electric
Power Steering Indicator (When
Equipped), Belt Slip, Engine
Overheat, Service Interval,
Service Engine Light

CVT & EPS Warning Indicators,
Fuel Injection Warning Indicator,
Parking Brake Indicator, Seat Belt
Indicator, Oil Pressure Indicator
Light, Water Temperature
Warning Indicator

System Diagnostic Light,
Coolant Temperature,
Park Brake Indicator, Service
Interval Warning Light

Low Oil Warning Light, High-
Temperature Warning Light



SERVICEABILITY (CONT.)				
DOWNTIME KILLS PRODUCTIVITY. SEE HOW THESE VEHICLES HAVE BEEN ENGINEERED TO BE SERVICED BACK TO PEAK CONDITION WITH EASE.				
Oil Dipstick The more accessible the oil and air filter, the less time and effort you need to change them.	Accessible without lifting bed or removing panels	Requires lifting bed or removing panels	Requires lifting bed or removing panels	Requires lifting bed or removing panels
Air Intake Better filters in proper locations will allow for better air filtration, providing cleaner air to the engine. Cleaner air in the engine leads to longer engine life.	Front Air Intake with Donaldson® Cyclonic Air Filter	Cyclonic Air Filter, Low Behind Right Passenger Door	Cyclonic Air Filter, Under Bed	Cyclonic Air Filter, Under Cargo Bed

* Disclaimer: All information has been obtained from publicly-available and reputable sources, including manufacturer websites and product manuals.

Club Car® and CARRYALL® are registered trademarks of Club Car, LLC. Kawasaki® and MULE® are registered trademarks of Kawasaki Heavy Industries, Ltd. Kubota® is a registered trademark of KUBOTA CORPORATION. John Deere® is a registered trademark of Deere & Company Corp. Kevlar® is a registered trademark of DUPONT SAFETY & CONSTRUCTION, INC. Donaldson® is a registered trademark of DONALDSON COMPANY, INC. Unless noted, all trademarks are the property of Polaris Industries Inc.

© 2023 Polaris Industries Inc.

