



**POLARIS®**  
PRO XD MID-SIZE GAS CREW



**KAWASAKI®**  
MULE® 4010 4X4 TRANS FE



**CLUB CAR®**  
CARRYALL® 1700 4WD



**JOHN DEERE®**  
XUV590M S4

**SAFETY** SAFETY IS NUMBER ONE FOR COMMERCIAL AND GOVERNMENT USERS, AND IMPORTANT TO CONSIDER WHEN PURCHASING A FLEET. SEE HOW THESE VEHICLES STACK UP TO KEEP YOUR EMPLOYEES SAFE.

<p><b>Standard Safety Features</b></p> <p>A horn and backup alarm are not always a stock product, but enhances safety on the job site.</p>	Horn, Backup Alarm	Horn	Horn (opt) Backup Alarm (opt)	Horn (opt) Backup Alarm (opt)
<p><b>Lighting</b></p> <p>Proper headlights and taillights provide improved visibility.</p>	Hi/Low 55W/60W Halogen Headlights, LED Taillights	35W Halogen Headlights, Tail/Brake Lights	37.5W Halogen Headlights	34W Halogen Headlights, 12W Tail/Brake Lights
<p><b>Body Colors</b></p> <p>Orange decals provide increased pedestrian visibility.</p>	Gray with Orange Graphics	Bright White	Dark Gray, Dark Green	Green/Yellow, Olive/Black, Camo
<p><b>Seatbelts</b></p> <p>More points on the seatbelt make the passenger more secure. Orange seatbelts improve visibility to ensure operators are wearing them at all times.</p>	Orange, 3-point	Orange, 3-point	Black, 2-point	Black, 3-point
<p><b>Top Speed</b></p> <p>Speed is often limited to meet jobsite requirements.</p>	40 mph (64 kph) (26 mph/42 kph from factory) with limiting options down to 15 mph (24 kph)	25 mph (40 kph)	25 mph (40 kph)	48 mph (77 kph)
<p><b>OPEI Certification</b></p> <p>OPEI Certification involves approved safety features including an occupant protective structure (OPS).</p>	Yes	N/A	N/A	N/A

**DURABILITY** DURABILITY IS KEY TO HELP PREVENT VEHICLE BREAKDOWNS AND TIME CONSUMING MAINTENANCE. SEE HOW THESE VEHICLES HAVE BEEN DURABLY ENGINEERED TO KEEP RUNNING LONGER.

<p><b>Engine</b></p>	Polaris® Prostar 570cc 4-cycle Gas	617cc 4-stroke 2 Cylinder	Kawasaki® 675cc 4-stroke 2 Cylinder	586cc Inline, 2 Cylinder, EFI
<p><b>Bed Box Dimensions</b></p> <p>A larger box bed will allow for hauling more or heavier goods.</p>	32 x 42 x 11.5 in (81.3 x 106.7 x 29.2 cm)	30.3 x 47.6 x 11.2 in (77 x 120.9 x 28.4 cm)	48 x 49.8 x 10.9 in (122 x 128 x 28 cm)	32.3 x 47.6 x 11.7 in (82 x 120.9 x 29.7 cm)
<p><b>Box Cargo Capacity</b></p> <p>More cargo capacity will allow for hauling larger loads, but not necessarily heavier loads.</p>	500 lb (226.8 kg)	401 lb (182 kg)	800 lb (363 kg)	500 lb (227 kg)
<p><b>Box Bed Material</b></p> <p>Heavy-duty poly will help reduce damage and rust to the box, reducing maintenance.</p>	Heavy-duty Poly	Steel	Aluminum Powder-coated Steel (opt)	Heavy-duty Poly
<p><b>Towing Capacity</b></p> <p>Having a high towing capacity allows you to trailer more goods and reduce trips on the jobsite.</p>	1,500 lb (680 kg)	1,200 lb (544 kg)	2,000 lb (907 kg)	1,500 lb (680 kg)
<p><b>Payload Capacity</b></p> <p>Having more payload will allow you to haul more goods and people.</p>	1,141 lb (517 kg)	1,330 lb (603 kg)	1,600 lb (726 kg)	900 lb (408 kg)



**POLARIS®**  
PRO XD MID-SIZE GAS CREW



**KAWASAKI®**  
MULE® 4010 4X4 TRANS FE



**CLUB CAR®**  
CARRYALL® 1700 4WD



**JOHN DEERE®**  
XUV590M S4

**DURABILITY (CONT.)**

DURABILITY IS KEY TO HELP PREVENT VEHICLE BREAKDOWNS AND TIME CONSUMING MAINTENANCE. SEE HOW THESE VEHICLES HAVE BEEN DURABLY ENGINEERED TO KEEP RUNNING LONGER.

<p><b>Drive System Type</b></p> <p>Auto engagement into all wheel drive helps when the rear tires slip, preventing getting stuck in problematic terrain. Turf mode allows for minimal impact on delicate terrain.</p>	Selectable Turf/2WD/4WD	Selectable 2WD/4WD	Auto 4WD	Selectable 2WD/4WD with Differential Locks
<p><b>Fuel Capacity</b></p> <p>More fuel allows you to work longer on one tank.</p>	9 gal (34 L)	6.3 gal (23.8 L)	6.5 gal (24.6 L)	7.4 gal (28 L)
<p><b>Ground Clearance</b></p> <p>More ground clearance helps clear more uneven terrain without bottoming out.</p>	11 in (25.4 cm)	7.7 in (19.6 cm)	8.2 in (20.8 cm)	9.3 in (23.62 cm)
<p><b>Seat Covering</b></p> <p>Stronger materials, like Kevlar®, are more damage, puncture, and wear resistant.</p>	Kevlar®-Reinforced Vinyl	Vinyl	Vinyl	Vinyl
<p><b>Driveline</b></p> <p>A driveline built with quality, durable parts will last longer in rugged environments and lead less to vehicle downtime.</p>	Heavy-duty Drive Shaft, CVT Boots and Wheel Bearings	UTV Standard Drive Shaft, CVT Boots and Wheel Bearings	UTV Standard Drive Shaft, CVT Boots and Wheel Bearings	UTV Standard Drive Shaft, CVT Boots and Wheel Bearings
<p><b>Tires</b></p> <p>Thicker walls (ply) help prevent flat tires. A square-profiled tire provides more even tread wear on hard-packed surfaces, and 4 common-size tires make replacing quick and simple.</p>	F: 8-ply 25 x 9-12 Crawler, Power Grip, Flat Profile R: 8-ply 25 x 9-12 Crawler, Power Grip, Flat Profile	F: 23 x 11-10 R: 23 x 11-10	F: 4-ply 25 x 10.5-12 All-Terrain R: 4-ply 25 x 10.5-12 All-Terrain	F: 4-ply 25 x 8-12 or 6-ply 26 x 8-14 R: 4-ply 25 x 10-12 or 6-ply 26 x 10-14
<p><b>SERVICEABILITY</b> DOWNTIME KILLS PRODUCTIVITY. SEE HOW THESE VEHICLES HAVE BEEN ENGINEERED TO BE SERVICED BACK TO PEAK CONDITION WITH EASE.</p>				
<p><b>Maintenance Interval (hours)</b></p> <p>The longer the maintenance interval, the less downtime your vehicle will need for repairs.</p>	200	250	100	100
<p><b>Warning Alarms</b></p> <p>More fault alarms notify the operator of potential issues that could cause serious damage to the vehicle.</p>	Low Oil Pressure, Belt Slip, Engine Overheat, Coolant Temperature Gauge, Seatbelt Indicator, Electric Power Steering Indicator (When Equipped)	Coolant Temp Warning Light, Oil Pressure Warning Light, Fuel Injection Warning Light, Parking Brake Warning Light, Power Steering Warning Light	Low Oil Warning Light, High-Temperature Warning Light	Engine Oil Temp, Seat Belt Indicator, Parking Brake Light

\* Disclaimer: All information has been obtained from publicly-available and reputable sources, including manufacturer websites and product manuals. Club Car® and CARRYALL® are registered trademarks of Club Car, LLC. Kawasaki® and MULE® are registered trademarks of Kawasaki Heavy Industries, Ltd. Kubota® is a registered trademark of KUBOTA CORPORATION. John Deere® is a registered trademark of Deere & Company Corp. Kevlar® is a registered trademark of DUPONT SAFETY & CONSTRUCTION, INC. Unless noted, all trademarks are the property of Polaris Industries Inc.

© 2023 Polaris Industries Inc.

WARNING: Polaris Pro XD vehicles can be hazardous to operate and are not intended for on-road use. All riders should always wear head protection - such as hard hats or a helmet - that is appropriate for operating conditions and intended usage, considering factors such as intended speed, unevenness of terrain, turns in path, weather, obstacles, and other traffic. DOT-approved helmet required for all riders when operating over 30mph. Always use seat belts and close doors (as equipped). Never engage in stunt driving, and avoid excessive speeds and sharp turns. Riding and alcohol/drugs don't mix. All riders should take a safety training course. Call 800-342-3764 for additional information.

**BUILD YOUR PRO XD AT**

[POLARIS.COM/PROXD](https://Polaris.com/PROXD)

