## PRO XD | PRO XD FULL-SIZE DIESEL CREW COMPARISON SUMMARY









KAWASAKI\* Mule\* pro-dxt eps diesel fe



KUBOTA° RTV- X1140



JOHN DEERE® XUV855M S4 DIESEL



CLUB CAR° Carryall° 1700 4WD Diesel

	PRU XU FULL-SIZE DIESEL CREW	MULE PRU-UXTEPS DIESELFE	RIV- XII4U	XUV855M 54 DIESEL	CARRYALL 1/UU 4WU DIESEL
SAFETY	SAFETY IS NUMBER ONE FOR COMMERCI	AL AND GOVERNMENT USERS, AND IMPORT	ANT TO CONSIDER WHEN PURCHASING A F	LEET. SEE HOW THESE VEHICLES STACK U	P TO KEEP YOUR EMPLOYEES SAFE.
Standard Safety Features A horn and backup alarm are not always a stock product, but enhances safety on the job site.	Horn Backup Alarm	Horn	Horn Backup Alarm	Horn	Backup Alarm
<b>Lighting</b> Proper headlights and tailights provide improved visibility.	Hi/Low 55W/60W Halogen Headlights, LED Tail/Break Lights	2 Halogen Headlights, Tail/Break Lights	37.5 Watt Halogen Headlights, Tail/Break Lights	Single-beam Halogen with Tailights	2 55W Halogen Headlight, Tailight (opt)
Body Colors  Orange decals provide increased pedestrian visibility.	Gray with Orange Graphics	Bright White	Kubota Orange, Realtree AP Camo	Green/Yellow, Camouflage, Olive/Black	Dark Gray, Dark Green
Seatbelts  More points on the seatbelt make the passenger more secure. Orange seatbelts improve visibility to ensure operators are wearing them at all times.	Orange, 3-point	Orange, 3-point	Black, 2-point	Black, 3-point	Black, 2-point
<b>Top Speed</b> Speed is often limited to meet jobsite requirements.	26 mph (42 kph) with limiting options down to 15 mph (24 kph)	30 mph (48 kph)	25 mph (40 kph)	32 mph (51 kph)	25 mph (40 kph)
OPEI Certification  OPEI Certification involves approved safety features including an occupant protective structure (OPS).	Yes	N/A	N/A	N/A	N/A
DURABILITY	DURABILITY IS KEY TO HELP PREVENT V	EHICLE BREAKDOWS AND TIME CONSUMIN	G MAINTENANCE. SEE HOW THESE VEHICLE	S HAVE BEEN DURABLY ENGINEERED TO H	EEP RUNNING LONGER.
Engine	Kubota 898cc tier 4 Diesel	993cc 3-cylinder 4 Stroke Diesel Engine	Kubota® D1105-E4-UV 3-Cylinder	Yanmar 854cc Diesel 4-cycle	Kubota 719cc 4-cycle 3 Cylinder
Bed Box Dimensions A larger box bed will allow for hauling more or heavier goods.	43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)	22.0 x 53.7 x 11.0 (56 x 135 x 27 cm)	Short Bed: 26 x 57.7 x 11.2 (660 x 1465 x 285) Long Bed: 51.1 x 57.7 x 11.2 in (1300 x 1465 x 285)	45 x 52 x 12 in (114.3 x 132 x 30.5 cm)	48 x 49.8 x 10.9 in (122 x 128 x 28 cm)
Box Cargo Capacity  More cargo capacity will allow for hauling larger loads, but not necessarily heavier loads.	1,250 lb (567 kg)	350 lb (159 kg)	Short Bed Config: 661 lb (300 kg) Long Bed Config: 1,102 lb (500 kg)	1,000 lb (454 kg)	800 lb (363 kg)
Box Bed Material  Heavy-duty poly will help reduce damage and rust to the box, reducing maintenance.	Heavy-duty Poly	Steel	Steel	Heavy-duty Poly	Aluminum, Powder-coated Steel (opt)
Towing Capacity  Having a high towing capacity allows you to trailer more goods and reduce trips on the jobsite.	2,500 lb (1134 kg)	2,000 lb (907 kg)	1,300 lb (590 kg)	1,500 lb (680 kg)	2,000 lb (907.2 kg)



## PRO XD | PRO XD FULL-SIZE DIESEL CREW COMPARISON SUMMARY









KAWASAKI° Mule° pro-dxt eps diesel fe



KUBOTA° RTV- X1140



JOHN DEERE® XUV855M S4 DIESEL



CLUB CAR° Carryall° 1700 4WD DIESEL

	PRO XD FULL-SIZE DIESEL CREW	MULE® PRO-DXT EPS DIESEL FE	RTV- X1140	XUV855M S4 DIESEL	CARRYALL® 1700 4WD DIESEL
DURABILITY (CONT.)	DURABILITY IS KEY TO HELP PREVENT V	EHICLE BREAKDOWNS AND TIME CONSUM	ING MAINTENANCE. SEE HOW THESE VEHIC	LES HAVE BEEN DURABLY ENGINEERED TO	KEEP RUNNING LONGER.
Payload Capacity  Having more payload will allow you to haul more goods and people.	1,950 lb (844 kg)	1,581 lb (717 kg)	1,629 lb (739 kg)	1,297 lb (588 kg)	1,600 lb (726 kg)
Drive System Type					
Auto engagement into all wheel drive helps when the rear tires slip, preventing getting stuck in problematic terrain. Turf mode allows for minimal impact on delicate terrain.	Selectable Turf/2WD/4WD	Selectable 2WD/ 4WD	Selectable 2WD/4WD with Differential Locks	Selectable 2WD/4WD with Differential Locks	IntelliTrak™ Automatic 4WD
Fuel Capacity  More fuel allows you to work longer on one tank.	11.5 gal (43.5 L)	7.9 gal (29.9 L)	7.9 gal (30 L)	7.3 gal (27.6 L)	6.5 gal (24.6 L)
Ground Clearance  More ground clearance helps clear more uneven terrain without bottoming out.	11 in (27.9 cm)	10.2 in (25.9 cm)	9.4 in (24 cm)	11 in (28 cm)	8.2 in (21 cm)
Seat Covering					
Stronger materials, like Kevlar®, are more damage, puncture, and wear resistant.	Kevlar®-Reinforced Vinyl	Vinyl	Vinyl	Vinyl	Vinyl
Driveline  A driveline built with quality, durable parts will last longer in rugged environments and lead less to vehicle downtime.	Heavy-duty Drive Shaft, CVT Boots and Wheel Bearings	UTV standard Drive Shaft, CVT Boots and Wheel Bearings	Heavy Duty Axle by Demon® Powersports, Thermoplastic Polyester Elastomar CV Boots	UTV standard Drive Shaft, CVT Boots and Wheel Bearings	UTV standard Drive Shaft, CVT Boots and Wheel Bearings
Tires					
Thicker walls (ply) help prevent flat tires. A square-	F: 8-ply 26 x 10-12 Duro Power Grip, Flat Profile	F: 26 x 9-12 4 ply	F: 6-ply 25 x 10-12 All-Terrain	F: 27x9-R14 Maxxis Big Horn Radials	F: 4-ply 25 x 10.5-12, All-Terrain
profiled tire provides more even tread wear on hard-packed surfaces, and 4 common-size tires make replacing quick and simple.	R: 8-ply 26 x 10-12 Duro Power Grip, Flat Profile	R: 26 x 11-12 4 ply	F: 6-ply 25 x 10-12 All-Terrain	R: 27x11-R14 Maxxis Big Horn Radials	R: 4-ply 25 x 10.5-12, All-Terrain
SERVICEABILITY	DOWNTIME KILLS PRODUCTIVITY. SEE H	OW THESE VEHICLES HAVE BEEN ENGINEE	RED TO BE SERVICED BACK TO PEAK COND	ITION WITH EASE.	
Maintenance Interval (hours)					
The longer the maintenance interval, the less downtime your vehicle will need for repairs.	200	250	200	200	100
Warning Alarms  More fault alarms notify the operator of potential issues that could cause serious damage to the vehicle.	Low Oil Pressure, Belt Slip, Engine Overheat, Parking Brake Indicator, Coolant Temperature Gauge, Engine Oil Pressure Indicator, Electric Power Steering Indicator (When Equipped), Service Interval, Service Engine Light	WaterTemp Warning,Oil Pressure Warning Light, Fuel Injection Warning Light, Parking Brake Warning Light, CVT & EPS Warning Light Seatbelt	Coolant Temperature Gauge, Engine Oil Pressure Indicator, Electrical Charge Light, Low Brake Fluid Indicator, Parking Brake Indicator, Seatbelt Indicator, Electric Power Steering Indicator	System Diagnostic Light, Coolant Temperature, Park Brake Indicator, Service Interval Warning Light	Low Oil Warning Light, High-Temperature Warning Light



## PROXD | PROXD FULL-SIZE DIESEL CREW COMPARISON SUMMARY









MULE® PRO-DXT EPS DIESEL FE



KUBOTA' RTV- X1140



XUV855M S4 DIESEL



CARRYALL® 1700 4WD DIESEL

SERVICEABILITY (CONT.)	DOWNTIME KILLS PRODUCTIVITY. SEE HOW THESE VEHICLES HAVE BEEN ENGINEERED TO BE SERVICED BACK TO PEAK CONDITION WITH EASE.					
Oil Dipstick  The more accessible the oil and air filter, the less time and effort you need to change them.	Accessible without lifting bed or removing panels	Requires lifting bed or removing panels	Requires lifting bed or removing panels	Requires lifting bed or removing panels	Requires lifting bed or removing panels	
Air Intake  Better filters in proper locations will allow for better air filtration, providing cleaner air to the engine. Cleaner air in the engine leads to longer engine life.	Front Air Intake with Donaldson® Cyclonic Air Filter	Element Cyclinic Air Filter, Under Rear Seat	Wix <sup>®</sup> Cyclinic Air Filter, Underneath Hood	Cyclonic Air Filter, Under Passenger Seat	Cyclonic Air Filter, Under Passenger Seat	

<sup>\*</sup> Disclaimer: All information has been obtained from publicly-available and reputable sources, including manufacturer websites and product manuals.

Club Car® and CARRYALL® are registered trademarks of Club Car, LLC. Kawasaki® and MULE® are registered trademarks of Kawasaki Heavy Industries, Ltd. Kubota® is a registered trademark of KUBOTA CORPORATION. John Deere® is a registered trademark of Deere & Company Corp. Kevlar® is a registered trademark of DUPONT SAFETY & CONSTRUCTION, INC. Donaldson® is a registered trademark of DONALDSON COMPANY, INC. WIX® is a registered trademark of MANN+HUMMEL FILTRATION TECHNOLOGY US LLC. DEMON POWERSPORTS® is a registered trademark of 2482265 Ontario Inc. CORPORATION CANADA. Unless noted, all trademarks are the property of Polaris Industries Inc.

© 2024 Polaris Industries Inc.