



POLARIS®  
PRO XD FULL-SIZE GAS CREW



KAWASAKI®  
MULE® PRO-FXT EPS



JOHN DEERE®  
XUV825M S4



CLUB CAR®  
CARRYALL® 1700 4WD

**SAFETY** SAFETY IS NUMBER ONE FOR COMMERCIAL AND GOVERNMENT USERS, AND IMPORTANT TO CONSIDER WHEN PURCHASING A FLEET. SEE HOW THESE VEHICLES STACK UP TO KEEP YOUR EMPLOYEES SAFE.

<p><b>Standard Safety Features</b></p> <p>A horn and backup alarm are not always a stock product, but enhances safety on the job site.</p>	Horn, Backup Alarm	Horn, Backup Alarm (opt)	Horn	Backup Alarm
<p><b>Lighting</b></p> <p>Proper headlights and taillights provide improved visibility.</p>	Hi/Low 55W/60W Halogen Headlights, LED Tail/Brake Lights	Halogen Headlights , LED Subheadlights, 55W Tail/Brake Lights	Single-beam 50W Halogen with Taillights	55W Halogen Headlight, Taillight (opt)
<p><b>Body Colors</b></p> <p>Orange decals provide increased pedestrian visibility.</p>	Gray with Orange Graphics	Timberline Green, Bright White	Green/Yellow, Camouflage, Olive/Black	Dark Gray, Dark Green
<p><b>Seatbelts</b></p> <p>More points on the seatbelt make the passenger more secure. Orange seatbelts improve visibility to ensure operators are wearing them at all times.</p>	Orange, 3-point	Black, 3-point	Black, 3-point	Black, 2-point
<p><b>Top Speed</b></p> <p>Speed is often limited to meet jobsite requirements.</p>	40 mph (64 kph) (26 mph/42 kph from factory) with limiting options down to 15 mph (24 kph)	45 mph (72 kph)	44 mph (70 kph)	25 mph (40 kph)
<p><b>OPEI Certification</b></p> <p>OPEI Certification involves approved safety features including an occupant protective structure (OPS).</p>	Yes	N/A	N/A	N/A

**DURABILITY** DURABILITY IS KEY TO HELP PREVENT VEHICLE BREAKDOWNS AND TIME CONSUMING MAINTENANCE. SEE HOW THESE VEHICLES HAVE BEEN DURABLY ENGINEERED TO KEEP RUNNING LONGER.

<p><b>Engine</b></p>	Polaris® ProStar 1,000cc 4-cycle Gas	812cc 4-stroke 3 Cylinder	Kawasaki® 812cc 4-cylinder	Kawasaki® 675cc 4-cycle 2 Cylinder
<p><b>Bed Box Dimensions</b></p> <p>A larger box bed will allow for hauling more or heavier goods.</p>	43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)	42.7 x 53.7 x 11 in (3-person) (108.5 x 136.4 x 27.9 cm 3-person) 22 x 53.7 x 11 in (6-person) (55.9 x 136.4 x 27.9 cm 6-person)	45 x 52 x 12 in (114.3 x 132 x 30.5 cm)	48.8 x 49.8 x 10.9 in (123 x 128 x 28 cm)
<p><b>Box Cargo Capacity</b></p> <p>More cargo capacity will allow for hauling larger loads, but not necessarily heavier loads.</p>	1,250 lb (567 kg)	350 lb (158 kg) (6-person)	1,000 lb (454 kg)	800 lb (363 kg)
<p><b>Box Bed Material</b></p> <p>Heavy-duty poly will help reduce damage and rust to the box, reducing maintenance.</p>	Heavy-duty Poly	Steel	Heavy-duty Poly	Aluminum, Powder-coated Steel (opt)
<p><b>Towing Capacity</b></p> <p>Having a high towing capacity allows you to trailer more goods and reduce trips on the jobsite.</p>	2,500 lb (1134 kg)	2,000 lb (907.2 kg)	1,500 lb (680 kg)	2,000 lb (907.2 kg)



**POLARIS®  
PRO XD FULL-SIZE GAS CREW**



**KAWASAKI®  
MULE® PRO-FXT EPS**



**JOHN DEERE®  
XUV825M S4**



**CLUB CAR®  
CARRYALL® 1700 4WD**

**DURABILITY (CONT.)**

DURABILITY IS KEY TO HELP PREVENT VEHICLE BREAKDOWNS AND TIME CONSUMING MAINTENANCE. SEE HOW THESE VEHICLES HAVE BEEN DURABLY ENGINEERED TO KEEP RUNNING LONGER.

<p><b>Payload Capacity</b></p> <p>Having more payload will allow you to haul more goods and people.</p>	2,050 lb (930 kg)	1,616 lb (733 kg)	1,400 lb (635 kg)	1,600 lb (817 kg)
<p><b>Drive System Type</b></p> <p>Auto engagement into all wheel drive helps when the rear tires slip, preventing getting stuck in problematic terrain. Turf mode allows for minimal impact on delicate terrain.</p>	Selectable Turf/2WD/4WD	Selectable 2WD/ 4WD	Selectable 2WD/4WD with Differential Locks	IntelliTrak™ Automatic 4WD
<p><b>Fuel Capacity</b></p> <p>More fuel allows you to work longer on one tank.</p>	11.5 gal (43.5 L)	7.9 gal (29.9L)	7.3 gal (27.6 L)	6.5 gal (24.6 L)
<p><b>Ground Clearance</b></p> <p>More ground clearance helps clear more uneven terrain without bottoming out.</p>	11 in (27.9 cm)	10.2 in (25.9 cm)	11 in (27.9 cm)	8.2 in (21 cm)
<p><b>Seat Covering</b></p> <p>Stronger materials, like Kevlar®, are more damage, puncture, and wear resistant.</p>	Kevlar®-Reinforced Vinyl	Vinyl	Vinyl	Vinyl
<p><b>Driveline</b></p> <p>A driveline built with quality, durable parts will last longer in rugged environments and lead less to vehicle downtime.</p>	Heavy-duty Drive Shaft, CVT Boots and Wheel Bearings	UTV standard Drive Shaft, CVT Boots and Wheel Bearings	UTV standard Drive Shaft, CVT Boots and Wheel Bearings	UTV standard Drive Shaft, CVT Boots and Wheel Bearings
<p><b>Tires</b></p> <p>Thicker walls (ply) help prevent flat tires. A square-profiled tire provides more even tread wear on hard-packed surfaces, and 4 common-size tires make replacing quick and simple.</p>	F: 8-ply 26 x 10-12 Duro Power Grip, Flat Profile R: 8-ply 26 x 10-12 Duro Power Grip, Flat Profile	F: 4-ply 26 x 9-12, All-Terrain R: 4-ply 26 x 11-12, All-Terrain	F: 27 x 9-14, Maxxis 2.0 Extreme Terrain Radials on Steel or Alloy Wheels R: 27 x 11-14, Maxxis Big-Horn Extreme Terrain Radials on Steel or Alloy Wheels	F: 4-ply 25 x 10.5-12, All-Terrain R: 4-ply 25 x 10.5-12, All-Terrain

**SERVICEABILITY**

DOWNTIME KILLS PRODUCTIVITY. SEE HOW THESE VEHICLES HAVE BEEN ENGINEERED TO BE SERVICED BACK TO PEAK CONDITION WITH EASE.

<p><b>Maintenance Interval (hours)</b></p> <p>The longer the maintenance interval, the less downtime your vehicle will need for repairs.</p>	200	100	100	100
<p><b>Warning Alarms</b></p> <p>More fault alarms notify the operator of potential issues that could cause serious damage to the vehicle.</p>	Coolant Temperature Gauge, Engine Oil Pressure Indicator, Seatbelt Indicator, Electric Power Steering Indicator (When Equipped), Belt Slip, Engine Overheat, Service Interval, Service Engine Light	CVT & EPS Warning Indicators, Fuel Injection Warning Indicator, Parking Brake Indicator, Seat Belt Indicator, Oil Pressure Indicator Light, Water Temperature Warning Indicator	System Diagnostic Light, Coolant Temperature, Park Brake Indicator, Service Interval Warning Light	Low Oil Warning Light, High-Temperature Warning Light



POLARIS®  
PRO XD FULL-SIZE GAS CREW



KAWASAKI®  
MULE® PRO-FXT EPS



JOHN DEERE®  
XUV825M S4



CLUB CAR®  
CARRYALL® 1700 4WD

SERVICEABILITY (CONT.)

DOWNTIME KILLS PRODUCTIVITY. SEE HOW THESE VEHICLES HAVE BEEN ENGINEERED TO BE SERVICED BACK TO PEAK CONDITION WITH EASE.

**Oil Dipstick**

The more accessible the oil and air filter, the less time and effort you need to change them.

Accessible without lifting bed or removing panels

Requires lifting bed or removing panels

Requires lifting bed or removing panels

Requires lifting bed or removing panels

**Air Intake**

Better filters in proper locations will allow for better air filtration, providing cleaner air to the engine. Cleaner air in the engine leads to longer engine life.

Front Air Intake with Donaldson® Cyclonic Air Filter

Cyclonic Air Filter, Low Behind Right Passenger Door

Cyclonic Air Filter, Under Bed

Cyclonic Air Filter, Under Cargo Bed

\* Disclaimer: All information has been obtained from publicly-available and reputable sources, including manufacturer websites and product manuals.

Club Car® and CARRYALL® are registered trademarks of Club Car, LLC. Kawasaki® and MULE® are registered trademarks of Kawasaki Heavy Industries, Ltd. Kubota® is a registered trademark of KUBOTA CORPORATION. John Deere® is a registered trademark of Deere & Company Corp. Kevlar® is a registered trademark of DUPONT SAFETY & CONSTRUCTION, INC. Donaldson® is a registered trademark of DONALDSON COMPANY, INC. Unless noted, all trademarks are the property of Polaris Industries Inc.

© 2024 Polaris Industries Inc.