



POLARIS®  
PRO XD FULL-SIZE GAS



KAWASAKI®  
MULE® 4010 4X4 FE



KUBOTA®  
RTV-XG850 SIDEKICK



JOHN DEERE®  
HPX615E



CLUB CAR®  
CARRYALL® 1500 4WD

**SAFETY** SAFETY IS NUMBER ONE FOR COMMERCIAL AND GOVERNMENT USERS, AND IMPORTANT TO CONSIDER WHEN PURCHASING A FLEET. SEE HOW THESE VEHICLES STACK UP TO KEEP YOUR EMPLOYEES SAFE.

<p><b>Standard Safety Features</b></p> <p>A horn and backup alarm are not always a stock product, but enhances safety on the job site.</p>	Horn Backup Alarm	Horn, Backup Alarm (opt)	Horn	Horn (opt) Backup Alarm (opt)	Reverse Buzzer (opt)
<p><b>Lighting</b></p> <p>Proper headlights and taillights provide improved visibility.</p>	Hi/Low 55W/60W Halogen Headlights, LED Tail/Brake Lights	35W Halogen Headlights, 21/5W Tail/Brake Lights	LED Headlights, Tail/Brake Lights (opt)	37W Halogen Headlights, 12W Tail/Brake Lights	37W Halogen Headlights, Tail/Brake Lights (opt)
<p><b>Body Colors</b></p> <p>Orange decals provide increased pedestrian visibility.</p>	Gray with Orange Graphics	Bright White	Orange, Camo, Green, Black	Green/Yellow	Dark Gray, Dark Green
<p><b>Seatbelts</b></p> <p>More points on the seatbelt make the passenger more secure. Orange seatbelts improve visibility to ensure operators are wearing them at all times.</p>	Orange, 3-point	Orange, 2-point	Black, 3-point	Black, 3-point	Black, 2-point
<p><b>Top Speed</b></p> <p>Speed is often limited to meet jobsite requirements.</p>	40 Mph (64 Kph) (26 Mph/42 Kph from factory) with limiting options down to 15 Mph (24 Kph)	25 mph (40 kph)	40 mph (65 kph)	25 mph (40 kph)	25 mph (40 kph)
<p><b>OPEI Certification</b></p> <p>OPEI Certification involves approved safety features including an occupant protective structure (OPS).</p>	Yes	N/A	N/A	N/A	N/A

**DURABILITY** DURABILITY IS KEY TO HELP PREVENT VEHICLE BREAKDOWNS AND TIME CONSUMING MAINTENANCE. SEE HOW THESE VEHICLES HAVE BEEN DURABLY ENGINEERED TO KEEP RUNNING LONGER.

<p><b>Engine</b></p>	Polaris® Prostar 1,000cc 4-cycle Gas	617cc 4-stroke 2 Cylinder	Kubota® 851cc 4-cycle 2 Cylinder	Kawasaki® 617cc 4-cycle Gas	Kawasaki® 719cc 4-stroke 3 Cylinder
<p><b>Bed Box Dimensions</b></p> <p>A larger box bed will allow for hauling more or heavier goods.</p>	43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)	46.3 x 51.6 x 11.4 in (117.6 x 131.1 x 28.9 cm)	40.5 x 57.5 x 11.4 in (1030 x 1465 x 290 cm)	45 x 52 x 12 in (114.3 x 132.1 x 30.5 cm)	48 x 49.8 x 10.9 in (122 x 157 x 28 cm)
<p><b>Box Cargo Capacity</b></p> <p>More cargo capacity will allow for hauling larger loads, but not necessarily heavier loads.</p>	1,250 lb (567 kg)	800 lb (362 kg)	1,000 lb (454 kg), *CA models 600 (272 kg)	1,000 lb (454 kg)	800 lb (363 kb) Standard Suspension, 1050 lb (476 kg) HD Suspension
<p><b>Box Bed Material</b></p> <p>Heavy-duty poly will help reduce damage and rust to the box, reducing maintenance.</p>	Heavy-duty Poly	Steel	Steel	Heavy-duty Poly	Aluminum, Powder-coated Steel (opt)
<p><b>Towing Capacity</b></p> <p>Having a high towing capacity allows you to trailer more goods and reduce trips on the jobsite.</p>	2,500 lb (1134 kg)	1,200 lb (544 kg)	2,000 lb (907 kg)	1,300 lb (590 kg)	2,000 lb (907 kg)



**POLARIS®**  
PRO XD FULL-SIZE GAS



**KAWASAKI®**  
MULE™ 4010 4X4 FE



**KUBOTA®**  
RTV-XG850 SIDEKICK



**JOHN DEERE®**  
HPX615E



**CLUB CAR™**  
CARRYALL™ 1500 4WD

**DURABILITY (CONT.)**

DURABILITY IS KEY TO HELP PREVENT VEHICLE BREAKDOWNS AND TIME CONSUMING MAINTENANCE. SEE HOW THESE VEHICLES HAVE BEEN DURABLY ENGINEERED TO KEEP RUNNING LONGER.

**Payload Capacity**

Having more payload will allow you to haul more goods and people.

1,900 lb (861 kg)

1,312 lb (595 kg)

1,435 lb (651 kg)

1,400 lb (635 kg)

1,200 lb (544 kg) Standard Suspension, 1,450 lb (658 kg) HD Suspension

**Drive System Type**

Auto engagement into all wheel drive helps when the rear tires slip, preventing getting stuck in problematic terrain. Turf mode allows for minimal impact on delicate terrain.

Selectable Turf/2WD/4WD

Selectable 2WD/4WD

Selectable 2WD/4WD with Differential Locks

Selectable 2WD/4WD with Differential Locks

IntelliTrack™ Automatic 4WD

**Fuel Capacity**

More fuel allows you to work longer on one tank.

11.5 gal (43.5L)

6.3 gal (23.8 L)

8.64 gal (32.7 L)

7.1 gal (27.6 L)

6.5 gal (24.6 L)

**Ground Clearance**

More ground clearance helps clear more uneven terrain without bottoming out.

11 in (27.9 cm)

6.9 in (17.5 cm)

9.8 in (24.8 cm)

6 in (15.2 cm)

8.2 in (20.8 cm)

**Seat Covering**

Stronger materials, like Kevlar®, are more damage, puncture, and wear resistant.

Kevlar®-Reinforced Vinyl

Vinyl

Vinyl

Vinyl

Vinyl

**Driveline**

A driveline built with quality, durable parts will last longer in rugged environments and lead less to vehicle downtime.

Heavy-duty Drive Shaft, CVT Boots and Wheel Bearings

UTV Standard Drive Shaft, CVT Boots and Wheel Bearings

UTV Standard Drive Shaft, CVT Boots and Wheel Bearings

UTV Standard Drive Shaft, CVT Boots and Wheel Bearings

UTV Standard Drive Shaft, CVT Boots and Wheel Bearings

**Tires**

Thicker walls (ply) help prevent flat tires. A square-profiled tire provides more even tread wear on hard-packed surfaces, and 4 common-size tires make replacing quick and simple.

F: 8-ply 26 x 10-12 Duro Power Grip, Flat Profile  
R: 8-ply 26 x 10-12 Duro Power Grip, Flat Profile

F: 4-ply 23 x 11-10  
R: 4-ply 23 x 11-10

F: 6-ply, 25 x 10-12 ATV or Flat Profile  
R: 6-ply, 25 x 10-13 ATV or Flat Profile

F: 24 X 9.5-10  
R: 24 x 10.5-10

F: 4-ply, 25 x 10.5-12 All-Terrain  
R: 4-ply, 25 x 10.5-12 All-Terrain

**SERVICEABILITY**

DOWNTIME KILLS PRODUCTIVITY. SEE HOW THESE VEHICLES HAVE BEEN ENGINEERED TO BE SERVICED BACK TO PEAK CONDITION WITH EASE.

**Maintenance Interval (hours)**

The longer the maintenance interval, the less downtime your vehicle will need for repairs.

200

250

100

100

100

**Warning Alarms**

More fault alarms notify the operator of potential issues that could cause serious damage to the vehicle.

Low Oil Pressure, Belt Slip, Engine Overheat, Coolant Temperature Gauge, Seatbelt Indicator, Electric Power Steering Indicator (When Equipped)

Coolant Temp Warning Light, Oil Pressure Warning Light, Fuel Injection Warning Light, Parking Brake Warning Light, Power Steering Warning Light

Coolant Temperature Gauge, Engine Oil Pressure Indicator, Electrical Charge Light, Low Brake Fluid Level Indicator, Parking Brake Indicator, Seat Belt Indicator, Electric Power Steering Indicator

Battery Indicator, Oil Pressure, Coolant Temperature Gauge

Low Oil Warning Light



**POLARIS®**  
PRO XD FULL-SIZE GAS



**KAWASAKI®**  
MULE® 4010 4X4 FE



**KUBOTA®**  
RTV-XG850 SIDEKICK



**JOHN DEERE®**  
HPX615E



**CLUB CAR®**  
CARRYALL® 1500 4WD

**SERVICEABILITY (CONT.)**

DOWNTIME KILLS PRODUCTIVITY. SEE HOW THESE VEHICLES HAVE BEEN ENGINEERED TO BE SERVICED BACK TO PEAK CONDITION WITH EASE.

**Oil Dipstick**

The more accessible the oil and air filter, the less time and effort you need to change them.

Accessible without lifting bed or removing panels

Requires lifting bed or removing panels

Requires lifting bed or removing panels

Requires lifting bed or removing panels

Requires lifting bed or removing panels

**Air Intake**

Better filters in proper locations will allow for better air filtration, providing cleaner air to the engine. Cleaner air in the engine leads to longer engine life.

Front Air Intake with Donaldson® Cyclonic Air Filter

Cyclonic Air Filter, Low Behind Right Hand Door

Cyclonic Air Filter, Under Bed Box

Cyclonic Air Filter, Under Passenger Seat

Cyclonic Air Filter, Under Bed Box

\* Disclaimer: All information has been obtained from publicly-available and reputable sources, including manufacturer websites and product manuals.

Club Car® and CARRYALL® are registered trademarks of Club Car, LLC. Kawasaki® and MULE® are registered trademarks of Kawasaki Heavy Industries, Ltd. Kubota® is a registered trademark of KUBOTA CORPORATION. John Deere® is a registered trademark of Deere & Company Corp. Kevlar® is a registered trademark of DUPONT SAFETY & CONSTRUCTION, INC. Donaldson® is a registered trademark of DONALDSON COMPANY, INC. Unless noted, all trademarks are the property of Polaris Industries Inc.

© 2024 Polaris Industries Inc.

WARNING: Polaris Pro XD vehicles can be hazardous to operate and are not designed for on-road use. All riders should always wear head protection - such as hard hats or a helmet - that is appropriate for operating conditions and intended usage, considering factors such as intended speed, unevenness of terrain, turns in path, weather, obstacles, and other traffic. DOT-approved helmet required for all riders when operating over 30mph. Always use seat belts and close doors (as equipped). Never engage in stunt driving, and avoid excessive speeds and sharp turns. Riding and alcohol/drugs don't mix. All riders should take a safety training course. Call 800-342-3764 for additional information.

**BUILD YOUR PRO XD AT**

[POLARIS.COM/PROXD](https://POLARIS.COM/PROXD)

