



PRO XD FULL-SIZE GAS



KAWASAKI® MULE PRO-FX



KUBOTA® RTV-XG850



CLUB CAR® CARRYALL 1500 4WD



JOHN DEERE® HPX615E



CAT® CUV82

DURABILITY

DURABILITY IS KEY TO HELP PREVENT VEHICLE BREAKDOWNS AND TIME CONSUMING MAINTENANCE. SEE HOW THESE VEHICLES HAVE BEEN DURABLY ENGINEERED TO KEEP RUNNING LONGER.

Engine

Polaris gas engines offer industry-leading power & performance.

✔	Polaris ProStar® 1000cc 4-cycle gas	812 cc 4-cycle gas	2-cylinders, 4 -cycle gas	Kawasaki® 4-cycle industrial grade gas	Kawasaki® 617 cc 4-cycle gas	50 hp 4 -cycle gas
---	-------------------------------------	--------------------	---------------------------	--	------------------------------	--------------------

Bed Box Dimensions (L x W x H)

A larger bed box will allow for hauling larger loads, but not necessarily heavier loads.

	43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)	42.7 x 53.7 x 11.0 in (108.4 x 136.4 x 27.9 cm)	40.5 x 57.5 x 11.4 in (102.9 x 146.1 x 70.9 cm)	48.0 x 49.8 x 10.9 in (122 x 128 x 28 cm)	✔ 45 x 12 x 52 in (114.3 x 30.5 x 132.0 cm)	41.5 in x 55.25 in x 11.75 in (105.4 x 140.3 x 29.9 cm)
--	---	---	---	---	---	---

Box Cargo Capacity

More cargo capacity will allow for hauling more or heavier goods.

✔	1,250 lb (567 kg)	1,000 lb (453.6)	1,000 lb (453.6)	800 lb (363 kg)	1,000 lb (454 kg)	1,000 lb (453.6 kg)
---	-------------------	------------------	------------------	-----------------	-------------------	---------------------

Box Bed Material

Heavy-duty poly will help reduce damage and rust to the box, reducing maintenance.

✔	Heavy-duty poly	✔ Heavy-duty poly	Steel (Spray-on opt.)	Powder-coated steel or aluminum	✔ Heavy-duty poly	Painted steel
---	-----------------	-------------------	-----------------------	---------------------------------	-------------------	---------------

Towing Capacity

Having a high towing capacity allows you to trailer more goods and reduce trips on the jobsite

✔	2,500 lb (1,134 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	1,300 lb (590 kg)	2,000 lb (907.2 kg)
---	---------------------	---------------------	---------------------	---------------------	-------------------	---------------------

Payload Capacity

Having more payload will allow you to haul more goods and people.

✔	1,900 lb (862 kg)	1,616 lb (733 kg)	1,435 lb (650.9 kg)	1,200 lb (544 kg) - Standard 1,450 lb (658 kg) - HD suspension	1,400 lb (635 kg)	1,000 lb (453.6 kg)
---	-------------------	-------------------	---------------------	---	-------------------	---------------------

Drive System Type

Automatic engagement into all wheel drive helps when the rear tires slip, preventing getting stuck in problematic terrain.

✔	AWD - Ultra Turf	Selectable 2WD/4WD	Limited slip front differential with foot operated rear differential lock	IntelliTrak™ Automatic 4x4	4WD	2WD/4WD/Electric rear locking differential
---	------------------	--------------------	---	----------------------------	-----	--

Fuel Capacity

More fuel allows you to work longer on one tank saving you time and money.

✔	11.5 gal (43.5L)	7.9 gal (29.9 L)	8.64 gal (32.7 L)	6.5 gal (24.6 L)	5.3 gal (20.1 L)	10 gal (37.8L)
---	------------------	------------------	-------------------	------------------	------------------	----------------

Ground Clearance

More ground clearance helps clear more uneven terrain without bottoming out.

✔	11 in (27.9 cm)	10.4 in (26.4 cm)	9.8 in (24.8 cm)	8.2 in (20.8 cm)	6 in (15.2 cm)	10.5 in (26.7 cm)
---	-----------------	-------------------	------------------	------------------	----------------	-------------------

Seat Covering

Stronger materials, like Kevlar®, are more damage, puncture, and wear resistant and last longer.

✔	Kevlar®-backed vinyl (Grey)	Vinyl	Vinyl	Vinyl	Vinyl	Vinyl
---	-----------------------------	-------	-------	-------	-------	-------

Driveline

A driveline built with quality, durable parts will last longer in rugged environments and lead to less vehicle downtime.

✔	Heavy-duty drive shaft, CVT boots and wheel bearings	UTV standard drive shaft, CVT boots and wheel bearings	UTV standard drive shaft, CVT boots and wheel bearings	UTV standard drive shaft, CVT boots and wheel bearings	UTV standard drive shaft, CVT boots and wheel bearings	UTV standard drive shaft, CVT boots and wheel bearings
---	--	--	--	--	--	--

Tires

Thicker walls (ply) help prevent flat tires. A flat profiled tire provides more even tread wear on hard surfaces which allows the tire to last longer.

✔	F: 8-ply 26 x 10-12 Duro® Power grip, Flat profile R: 8-ply 26 x 10-12 Duro® Power grip, Flat profile	F: 26 x 9.00-12, Round profile R: 26 x 11.00-12, Round profile	F: 6-ply 25 x 10-12 ATV or HDWS, Flat profile R: 6-ply 25 x 10-12 ATV or HDWS, Flat profile	F: 4-ply All-terrain, 25 x 10.5 - 12 Flat profile R: 4-ply All-terrain, 25 x 10.5 - 12 Flat profile	F: 24 x 9.5-10 Round profile R: 24 x 10.5-10 Round profile	F: 25 x 10.5-12 Standard utility R: 25 x 10.5-12 Standard utility
---	--	---	--	--	---	--

