



BULLETIN#: PE774

ENGINE: E115DHLIS

BOAT TYPE: Pontoon

DATE OF TEST: 3/31/09





Bombardier Recreational Products Inc. 10101 Science Drive Sturtevant, WI 52177 www.evinrude.com



Godfrey Marine 4500 Middlebury Street Elkhart, Indiana 46516 574-522-8381

www.sweetwaterboats.com



2010 Sweetwater 2386 DF

BOAT				
2010 Sweetwater 2386 DF				
Material:	Aluminum			
Length:	23' 6"			
Beam:	8' 6"			
Weight w/o Engine:	1745 LBS Dry			
Maximum HP:	135 HP			
Fuel Capacity:	24 Gallons			
Transom Height:	20" Shaft			
Steering:	Cable			

ENGINE				
2010 Evinrude® ETEC® 115 HP HO				
Engine Type:	60° V4			
Horsepower:	Factory Tuned			
Displacement:	105 Cu. In.			
Induction:	ETEC DFI			
Operating Range:	5500-6000 RPM			
Weight:	390 LBS Dry Weight			
Gear Ratio:	2.00:1			

BRP Rogue™				
Material:	Stainless Steel			
Diameter/Pitch:	13 1/2" x 13"			
No. of Blades:	4			
Part Number:	763957			
MOUNTING HEIGHT				
Hole Position:	#3			
Jack Plate:	N/A			
Motor Height	N/A			

PROPELLER

PERFORMANCE DATA					
RPM	MPH	GPH	MPG	RANGE	
600	2.2	0.18	11.9	258	
1000	3.6	0.35	10.1	219	
1500	5.5	0.76	7.2	156	
2000	7.2	1.21	6.0	129	
2500	9.4	2.07	4.5	98	
3000	14.0	3.21	4.4	94	
3500	17.6	4.59	3.8	83	
4000	20.9	6.29	3.3	72	
4500	24.5	7.71	3.2	69	
5000	27.2	8.73	3.1	67	
5500	30.3	10.39	2.9	63	
5700	31.7	10.79	2.9	63	
Range (Miles) Based On 90% Fuel Capacity					

TEST CONDITIONS		
Water Conditions:	Light Chop	
Wind Velocity:	10 MPH	
Air Temperature:	60° F	
Fuel Load:	12 Gal	
Weight:	1 Man, Fuel, test & safety gear	

PERFORMANCE SUMMARY

Top Speed: 31.7 MPH

Best Fuel Efficiency: 6.0 MPG with a range of 129 Miles @

Acceleration: 3.5 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by

NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering. © 2009 BRP US Inc. All rights reserved.

