

PERFORMANCE BULLETIN



YPB#: PB_HUR_SunDeck217OB_F150XB_2017-08-28_DCK

Test Date 8/28/17



Hurricane

Boat Manufactured By:


Hurricane Boats • 4500 Middlebury Street • Elkhart, IN 46516
574-522-8381 • www.hurricaneboats.com

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.7	0.7	6.71
1500	6.0	1.2	5.00
2000	7.4	1.9	3.90
2500	8.6	3.1	2.77
3000	13.6	4.4	3.09
3500	21.4	5.5	3.89
4000	26.9	6.9	3.90
4500	31.4	8.7	3.61
5000	35.7	10.6	3.37
5500	40.4	14.7	2.75
5800	42.2	16.0	2.64

0~20 MPH

5.06



Test performed and verified by Yamaha Applications Engineers.



Hurricane® SunDeck 217 OB

Length	21' 5"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,850 lbs
Maximum HP	225
Fuel Capacity	49 gal
Weight as Tested	4,148 lbs

F150XB

Horsepower	150 HP
Induction	EFI
Displacement	2.7 L
Weight	489 lbs
Gear Ratio	2.00:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER/S

Series	Reliance®
Diameter/Pitch	14-1/4 x 17
Yamaha Part #	68F-45972-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	71 / 74° F
Elevation (in feet above sea level)	840'
Wind Velocity	5-10 mph

Comments: Test weight includes 45 gallons of fuel, 1 battery, safety and test gear.

Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.

For more information

Yamaha Motor Corporation, U.S.A.

OEM Division, Marine Group

1270 Chastain Road NW

Kennesaw, GA 30144 • (800) 88-YAMAHA

For other Performance Bulletins, visit www.yamaha-motor.com.

© 2017 Yamaha Motor Corporation, U.S.A. All rights reserved.