
# Yamaha Performance Bulletin

YPB#: PB HUR SunDeck2400OB F250XCA 5-4-10 DCK Test Date: 5/4/10



# **Performance Data**

RPM	MPH	GPH	MPG
1000	5.3	1.1	4.82
1500	7.3	1.9	3.84
2000	8.5	3.3	2.58
2500	10.3	4.7	2.19
3000	14.8	6.2	2.39
3500	28.9	8.4	3.44
4000	33.8	11.3	2.99
4500	38.3	14.3	2.68
5000	42.4	18.7	2.27
5500	47.1	22.8	2.07
5900	49.5	23.1	2.14



Test performed and verified by Yamaha Application Engineers.

#### For More Information:

Yamaha Motor Corporation, U.S.A. • OEM Division, Marine Group 1270 Chastain Road NW • Kennesaw, GA 30144 • (800) 88-YAMAHA For other Performance Bulletins, visit www.yamaha-motor.com. © 2009 Yamaha Motor Corporation, U.S.A. All rights reserved.



### Hurricane® SunDeck 2400 OB®

Length	24'
Beam	8' 6"
Dry Weight (Boat Mfr. Published)	3,735 lbs.
Maximum HP	300 hp
Fuel Capacity	77 gals.
Weight as Tested (Approximate)	5,188 lbs.



**Boat Manufactured By:** 

Hurricane Deckboats • 4500 Middlebury Street • Elkhart, IN 46516 574-522-8381 • www.hurricaneboats.com

#### Yamaha F250XCA

Horsepower	250
Displacement	4.2 L
Weight (Catalog Published)	558 lbs.
Gear Ratio	1.75

## **Engine Mounting Height**

Mounting Hole Position	#1
Anti-Ventilation Plate Height	2-1/2" Above Bottom

#### **Propeller**

Series	Saltwater Series II/SDS
Diameter/Pitch	15-1/2 x 17
Yamaha Part #	6CE-45978-00-00
Propeller Material	Polished Stainless Steel

#### **Test Conditions**

Number of People	2
Air / Water Temperature (Fahrenheit)	64° / 54°
Elevation	595'
Wind Velocity	5-10 MPH

Comments: Test weight includes 50 gallons of fuel, 1 battery, safety and test equipment. Fuel consumption data gathered with Yamaha Command Link® fuel management system. Zero-to-30 speed data gathered with Yamaha speedometer. Other speed data gathered with GPS receiver.

Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. For boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies of their products are for identification purposes only, and are not intended to be an endorsement.