

PERFORMANCE BULLETIN

Boat Manufactured By:



www.hurricaneboats.com

HURRICANE FUNDECK 236 SFL

Length	23' 6"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,350 lbs
Maximum HP	250 hp
Fuel Capacity	48 gal
Weight as Tested	4,673 lbs

VF250XA

Horsepower	250 hp	
Induction	EFI/VCT/DOHC	
Displacement	4.2L	
Weight (Estimated)	555 lbs	
Gear Ratio	1.75:1	

ENGINE MOUNTING HEIGHT

Mounting Hole Position #2

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15 3/4 x 15
Yamaha Part #	6CE-45976-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

umber of People	2
Air / Water Temperature	80° F / 73° F
(Fahrenheit)	80 1773 1
Elevation (in feet above sea level)	850'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 40 gallons of fuel, 1 battery, safety and test gear.

YPB#: PB_HUR_FunDeck 236 SFL_VF250XA_8.9.19_DCK



Engine: Yamaha VF250XA

Boat: Hurricane FunDeck 236 SFL

Configuration: Single Test Date: 9-Aug-2019



PERFORMANCE DATA

МРН	GPH	MPG
4.7	1.3	3.58
6.9	2.2	3.11
8.0	3.4	2.37
10.8	4.7	2.29
13.7	5.6	2.45
21.5	7.2	2.98
28.8	9.7	2.98
32.7	12.7	2.57
36.5	14.7	2.49
39.8	19.0	2.10
44.3	23.1	1.92
conds		
	4.7 6.9 8.0 10.8 13.7 21.5 28.8 32.7 36.5 39.8 44.3	4.7 1.3 6.9 2.2 8.0 3.4 10.8 4.7 13.7 5.6 21.5 7.2 28.8 9.7 32.7 12.7 36.5 14.7 39.8 19.0 44.3 23.1

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data or pive specifications and performance Bulletin may or may not have been performed using Yamaha Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.