

Boat Manufactured By:

rricane /iddlebury St. • Elkhart, IN 46516

(574) 522-8381 www.hurricaneboats.com

HURRICANE SUNDECK SPORT 185

Length	19' 2"
Beam	7' 8"
Dry Weight (Boat Mfr. Pub)	2,150 lbs
Maximum HP	115 hp
Fuel Capacity	22 gal
Weight as Tested	3,098 lbs

F90LB

Horsepower	90 hp
Induction	EFI/DOHC
Displacement	1832 CC
Weight (Estimated)	353 lbs
Gear Ratio	2.15:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
PROPELLER(S)	
Series	Talon GP™
Diameter x Pitch	13-1/4 x 16
Yamaha Part #	6FP-45945-00-00
Propeller Material	Aluminum

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	74° F / 72° F
Elevation (in feet above sea level)	850'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 12 gallons of fuel, 1 battery, safety and test gear.

YPB#: PB_HUR_SunDeck Sport 185_F90LB_8.9.19_DCK

PERFORMANCE BULLETIN



Engine: Yamaha F90LB **Boat:** Hurricane SunDeck Sport 185 **Configuration:** Single Test Date: 9-Aug-2019



PERFORMANCE DATA

RPM MPH GPH MPG 1000 4.2 0.5 8.3 1500 5.7 0.8 7.06 2000 7.1 1.2 6.13 2500 8.2 1.9 4.41 3000 13.9 2.6 5.45 3500 20.5 3.1 6.6 4000 24.6 3.7 6.73 4500 29.5 4.7 6.34 5000 36.8 7.6 4.84 5900 36.8 7.6 3.99				
15005.70.87.0620007.11.26.1325008.21.94.41300013.92.65.45 350020.53.16.6 400024.63.76.73450029.54.76.345000335.95.59550036.87.64.84 590038.39.63.99	RPM	МРН	GPH	MPG
20007.11.26.1325008.21.94.41300013.92.65.45 350020.53.16.6 400024.63.76.73450029.54.76.345000335.95.59550036.87.64.84 590038.39.63.99	1000	4.2	0.5	8.3
25008.21.94.41300013.92.65.45350020.53.16.6400024.63.76.73450029.54.76.345000335.95.59550036.87.64.84590038.39.63.99	1500	5.7	0.8	7.06
300013.92.65.45350020.53.16.6400024.63.76.73450029.54.76.35000335.95.59550036.87.64.84590038.39.63.99	2000	7.1	1.2	6.13
350020.53.16.6400024.63.76.73450029.54.76345000335.95.59550036.87.64.84590038.39.63.99	2500	8.2	1.9	4.41
4000 24.6 3.7 6.73 4500 29.5 4.7 6.34 5000 33 5.9 5.59 5500 36.8 7.6 4.84 5900 38.3 9.6 3.99	3000	13.9	2.6	5.45
4500 29.5 4.7 6.34 5000 33 5.9 5.59 5500 36.8 7.6 4.84 5900 38.3 9.6 3.99	3500	20.5	3.1	6.6
5000 33 5.9 5.59 5500 36.8 7.6 4.84 5900 38.3 9.6 3.99	4000	24.6	3.7	6.73
5500 36.8 7.6 4.84 5900 38.3 9.6 3.99	4500	29.5	4.7	6.34
5900 38.3 9.6 3.99	5000	33	5.9	5.59
	5500	36.8	7.6	4.84
0~20 MPH: 5.02 seconds	5900	38.3	9.6	3.99
0~20 MPH: 5.02 seconds	3900	50.5	5.0	3.99
	0~20 MPH: 5.02 se	conds		

NOTICE TO CONSUMER The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat's gitter and operators. The soft section of the performance data on your specific hoad/regine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engines without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.