



# MRZR® D2 & MRZR® D4

TURBO DIESEL — TRANSPORTABLE, AGILE, MOBILITY.

### SUSTAINMENT:

- Spares: SOFSA, DLA, GSA, NAMSA, DIRECT
- Technical Support Around the Globe
- Mechanic and Operator Training

### FIELDED BY:

- U.S. and Allied Military
- **■** Law Enforcement Agencies
- **■** Emergency Response Teams

### **PROCUREMENT:**





GS-07F-0398M

031717 1 01

DLA CONTRACT: LTCSPM8EC-13-D-0016



# **SPECIFICATIONS**

		M <i>RZR</i> ° D2 TURBO DIESEL	M <i>RZR</i> ° D4 TURBO DIESEL
ENGINE	ENGINE TYPE	4-STROKE SOHC, THREE CYLINDER, TURBO DIESEL	4-STROKE SOHC, THREE CYLINDER, TURBO DIESEL
	DISPLACEMENT	993CC	993CC
	FUEL SYSTEM	MECHANICAL FUEL INJECTION	MECHANICAL FUEL INJECTION
	COOLING	LIQUID	LIQUID
DRIVE	TRANSMISSION/FINAL DRIVE	AUTOMATIC CVT P/R/N/L/H	AUTOMATIC CVT P/R/N/L/H
	DRIVE SYSTEM	ON-DEMAND TRUE AWD / 2WD	ON-DEMAND TRUE AWD / 2WD
SUSPENSION	FRONT SUSPENSION	INDEPENDENT DUAL A- ARM 12" (30.5 CM) TRAVEL	INDEPENDENT DUAL A- ARM 12" (30.5 CM) TRAVEL
	REAR SUSPENSION	INDEPENDENT TRAILING ARM 12" (30.5 CM) TRAVEL	INDEPENDENT TRAILING ARM 12" (30.5 CM) TRAVEL
BRAKES	FRONT/REAR BRAKES	4-WHEEL HYDRAULIC DISC WITH DUAL-BORE FRONT AND SINGLE-BORE REAR CALIPERS	4-WHEEL HYDRAULIC DISC WITH DUAL-BORE FRONT AND SINGLE-BORE REAR CALIPERS
	PARKING BRAKE	PARK IN TRANSMISSION	PARK IN TRANSMISSION
TIRES/ WHEELS	FRONT TIRES	DWT MOAPA	DWT MOAPA
	REAR TIRES	DWT MOAPA	DWT MOAPA
	WHEEL AND TIRE SIZE	26" X 9" R14	26" X 9" R14
DIMENSIONS/CAPACITIES	WHEELBASE	79.5" (201.9 CM)	107" (271.9 CM)
	CURB WEIGHT	1,887 LBS. (856 KG)	2,100 LBS. (952.54 KG)
	OVERALL VEHICLE SIZE (L X W X H)	113 X 59.5 X 73.8 / 60" (COLLAPSED) (287 X 151.1 X 187.5 / 152.4 CM) (COLLAPSED)	140 X 59.5 X 73.8 / 60" (COLLAPSED) (355.6 X 151.1 X 187.5 / 152.4 CM) (COLLAPSED)
	GROUND CLEARANCE	12.5" (31.75 CM)	12" (30.48 CM)
	FUEL CAPACITY	9.5 GAL. (39 L)	9.5 GAL. (36 L)
	BED BOX DIMENSIONS (L X W X H)	32.3 X 49 X 20.4" (82 X 124.5 X 51.8 CM)	32.3 X 49 X 20.4" (82 X 124.5 X 51.8 CM)
	REAR CARGO CAPACITY	500 LBS. (226.8 KG)	500 LBS. (226.8 KG)
	PAYLOAD (Operators & Cargo)	1,000 LBS. (453.6 KG)	1,500 LBS. (680.4 KG)
	HITCH TOWING RATING	1,500 LBS. (680.4 KG)	1,500 LBS. (680.4 KG)
	HITCH/TYPE	2" STANDARD RECEIVER	2" STANDARD RECEIVER
	HITCH TOWING RATING	1,500 LBS. (680.4 KG)	1,500 LBS. (680.4 KG)
FEATURES	ELECTRONIC POWER STEERING	STANDARD	STANDARD
	AIRCRAFT TIE-DOWNS	FRONT AND REAR OF VEHICLE	FRONT AND REAR OF VEHICLE
	CARGO SYSTEM	POLARIS METAL RACKS WITH QUICK RAIL SYSTEM	POLARIS METAL RACKS WITH QUICK RAIL SYSTEM
	WINCH	POLARIS 4,500 LB. (2,041 KG) WINCH	POLARIS 4,500 LB. (2,041 KG) WINCH
	LIGHTING	WHITE LED (ON/OFF), BLACKOUT DRIVE, IR LIGHT	WHITE LED ( ON/OFF ), BLACKOUT DRIVE, IR LIGHT
	INSTRUMENTATION	DIGITAL GAUGE, KEYLESS IGNITION, SPEEDOMETER, ODOMETER, TACHOMETER, TRIPMETER, HOUR METER, CLOCK, GEAR INDICATOR, FUEL GAUGE, HI-TEMP/LOW-BATT LIGHTS, DC OUTLETS (2)	DIGITAL GAUGE, KEYLESS IGNITION, SPEEDOMETER, ODOMETER, TACHOMETER, TRIPMETER, HOUR METER, CLOCK, GEAR INDICATOR, FUEL GAUGE, HI-TEMP/LOW-BATT LIGHTS, DC OUTLETS (3)
	ALTERNATOR	12 V (107 AMP MAX OUTPUT)	12 V (107 AMP MAX OUTPUT)
COLOR	COLOR	MILITARY TAN	MILITARY TAN

### MRZR® D2



### MRZR® D4







## **INTERNAL AIR TRANSPORT:**

MIL-STD 209K









All pricing, specifications, claims and information contained in this brochure are based on information available at the time of publication. Polaris assumes no responsibility for any inaccuracies, opinion, or omissions in those publications. All pricing, specifications, and descriptions are subject to change without notice, and Polaris assumes no responsibility for changes in pricing or specifications. ©2018 Polaris Industries Inc.

