

Lube Specifications Chart Service Manual

Publication Printed 01/19/2022

© Copyright Polaris Inc. All information contained within this publication is based on the latest product information at the time of publication. Due to constant improvements in the design and quality of production components, some minor discrepancies may result between the actual vehicle and the information presented in this publication. Depictions and/or procedures in this publication are intended for reference use only. No liability can be accepted for omissions or inaccuracies. Any reprinting or reuse of the depictions and/or procedures contained within, whether whole or in part, is expressly prohibited. Printed in U.S.A.

SNOWMOBILE SERVICE PRODUCTS AND LUBRICANTS

MAINTENANCE PRODUCT PART NUMBERS

PRODUCT		PART NUMBER
	Quart	2877882
	Gallon	2877883
VES Synthotic 2 Cycle Oil	2.5 Gallon	2877884
VES Synthetic 2-Cycle Oil	16 Gallon	2877885
	55 Gallon	2877886
	330 Gallon	2877892
	Quart	2883733
	Gallon	2883732
VES Extreme Synthetic 2-Cycle Oil	16 Gallon	2883734
	55 Gallon	2883735
	330 Gallon	2883736
	Quart	2882201
	Gallon	2882202
Polaris Blue Synthetic Blend 2-Cycle Oil	16 Gallon	2882203
	55 Gallon	2882205
	330 Gallon	2882206
Vintage 2-Stroke Snowmobile Engine Oil	Quart	2889400
	Quart	2876244
	Gallon	2876245
PS-4 Engine Oil (4 stroke)	PS-4 Engine Oil Keg (16 Gallon)	2876247
	Drum (55 Gallon)	2876246
	Tote (330 Gallon)	2878814
	Quart	2873105
Synthetic Chaincase Lubricant	Gallon	2873106
	2.5 Gallon	2872952
	Quart	2880514
50/50 Extended Life Antifreeze	Gallon	2880513
	55 Gallon	2880512
Shock Oil - 5W - Walker Evans	Quart	2874522
Charle Cit FIM Face	Quart	2870995
Shock Oil - 5W - Fox	2.5 Gallon	2872279
Brake Fluid - DOT 4	12 oz	2872189
Fogging Oil (Aerosol)	12 oz	2870791
Drawaitura All Canada Canada	3 oz. Grease Gun Kit	2871312
Premium All Season Grease	14 oz. Tube	2871423
Starter Grease	2 oz	2871460
Carbon Clean	12 oz	2881413
Fuel Stabilizer	12 oz	2881416
Three Bond Sealant	5 oz	2871557

CHAPTER 3 SNOWMOBILE LUBE CHART

SNOWMOBILE LUBE CHART 2022	
SNOWMOBILE LUBE CHART 2021	3.4
SNOWMOBILE LUBE CHART 2020	
SNOWMOBILE LUBE CHART 2019	
SNOWMOBILE LUBE CHART 2018	
SNOWMOBILE LUBE CHART 2017	3.9
SNOWMOBILE LUBE CHART 2016	3.10
SNOWMOBILE LUBE CHART 2015	3.11
SNOWMOBILE LUBE CHART 2014	3.12
SNOWMOBILE LUBE CHART 2013	3.13
SNOWMOBILE LUBE CHART 2012	3.14
SNOWMOBILE LUBE CHART 2011	3.15
SNOWMOBILE LUBE CHART 2010	3.16
SNOWMOBILE LUBE CHART 2009	3.17
SNOWMOBILE LUBE CHART 2008	3.18
SNOWMOBILE LUBE CHART 2007	3.19
SNOWMOBILE LUBE CHART 2006	3.20
SNOWMOBILE LUBE CHART 2005	3.21
SNOWMOBILE LUBE CHART 2004	3.22
SNOWMOBILE LUBE CHART 2003	3.23
SNOWMOBILE LUBE CHART 2002	
SNOWMOBILE LUBE CHART 2001	
SNOWMOBILE LUBE CHART 2000	3.26
SNOWMOBILE LUBE CHART 1999	3 27

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine Polaris PS-4	_	-	_	N/A	N/A
	interval	50 hour	_	_	_		
	capacity		8.96 oz / 265 mL	_	_		
550 PRO-RIDE	interval	3.05 quarts / 2.89 liters	500 mile break in, 1500 miles (2400 km)	-	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		11 oz / 325.3 ml	_	_	refer to service manual for proper filling	5.7 quarts / 5.4 liters
600R	interval	N/A	500 mile break in, 1500 miles (2400 km)	-	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 ml	_	_	refer to service manual for proper filling	4 quarts / 3.8 liters
600 AXYS Trail Performance/ Crossover	interval	3.9 quarts / 3.7 liters	500 mile break in, 1500 miles (2400 km)	-	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		_	_	_	refer to service manual for proper filling	5.3 - 5.5 quarts / 5 - 5.3 liters
850 AXYS Deep Snow	interval	3.9 quarts / 3.7 liters	_	-	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		_	29 oz / 850 mL	_	refer to service manual for proper filling	8 quarts / 7.6 liters
Titan 800	interval	3.8 quarts / 3.6 liters	_	4000 miles (6400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL	_	_	refer to service manual for proper filling	4 quarts / 3.8 liters
600 Matryx Indy Cross Country	interval	3.75 quarts / 3.5 liters	500 mile break in, 1500 miles (2400 km)	-	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 ml	_	_	refer to service manual for proper filling	4 quarts / 3.8 liters
650/850 Matryx Trail Performance/ Crossover	interval	3.75 quarts / 3.5 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
650/850 Matryx Deep	capacity	3.9 quarts / 3.7 liters	_	-	-	refer to service manual for proper filling	Slash Models - 5.6 quarts / 5.3 liters Standard Models - 6.25 quarts / 6.05 liters
Snow	interval		-	-	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		_	_	_	refer to service manual for proper filling	5.6 quarts / 5.3 liters
Matryx Boost Deep Snow	interval	3.9 quarts / 3.7 liters	_	-	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

						T	
MODEL		VES SYNTHETIC 2- CYGLE OIL 2877882	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
	capacity	20 oz(.6L) dry engine Polaris PS-4	_	_	_		
Indy 120	interval	50 hour	_	_	_	N/A	N/A
	capacity		9oz / 266 mL	_	_	refer to service manual for proper filling	
550 Indy	interval	3.05 quarts / 2.89 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9oz / 266 mL	_	_	refer to service manual for proper filling	
550 Voyageur	interval	3.05 quarts / 2.89 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		10 oz / 296 mL	_	_	refer to service manual for proper filling	5 quarts / 4.7 liters
600 Indy	interval	3.9 quarts / 3.7 liters	500 mile break in, 1500 miles (2400 km)	-	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_	_	refer to service manual for proper filling	5.7 quarts / 5.4 liters
600R	interval	3 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL	_	_	refer to service manual for proper filling	4 quarts / 3.8 liters
600 AXYS Trail Performance/ Crossover	interval	3.9 quarts / 3.7 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 ml	_	_	refer to service manual for proper filling	4 quarts / 3.8 liters
850 AXYS Trail Performance/ Crossover	interval	3.9 quarts / 3.7 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		_	_	_	refer to service manual for proper filling	5.3 quarts / 5 liters
600 AXYS Deep Snow	interval	3.9 quarts / 3.7 liters	_	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 ml (If Equipped)		_	refer to service manual for proper filling	5.3 - 5.7 quarts / 5 - 5.4 liters
850 AXYS Deep Snow	interval	3.9 quarts / 3.7 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 ml	_	_	refer to service manual for proper filling	4 quarts / 3.8 liters
650/850 Matryx Trail Performance	interval	3.75 quarts / 3.5 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Titan	capacity	3.8 quarts / 3.6 liters	_	28 oz / 828 mL	_	refer to service manual for proper filling	8 quarts / 7.6 liters

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine Polaris PS-4	_	_	_	N/A	N/A
	interval	50 hour	<u> </u>	_	_	refer to service manual	
550 Indy	interval	3.05 quarts / 2.89 liters	9 oz / 266 mL 500 mile break in, 1500 miles (2400 km)		2000 miles (3200 km)	for proper filling High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	_	refer to service manual for proper filling	
550 Voyageur	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		20 oz / 592 mL	_	_	refer to service manual for proper filling	
550 Widetrak	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	_	refer to service manual for proper filling	5 quarts / 4.7 liters
600 Indy	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_	_	refer to service manual for proper filling	5.7 quarts / 5.4 liters
600R	interval	3 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL	_	_	refer to service manual for proper filling	4 — 6.3 quarts / 3.8 —6 liters
600/800 Rush, Switchback, Voyageur, RMK	interval	3.9 quarts / 3.7 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 ml	_	_	refer to service manual for proper filling	4 quarts / 3.8 liters
850 AXYS Trail Performance/ Crossover	interval	3.9 quarts / 3.7 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 ml	_		refer to service manual for proper filling	5.5 quarts / 5.2 liters
850 AXYS Deep Snow	3.9 quarts / 3.7 lit	3.9 quarts / 3.7 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		_	29 oz / 850 mL	_	refer to service manual for proper filling	8 quarts / 7.6 liters
Titan	interval	3.8 quarts / 3.6 liters	-	500 mile break in, 4000 miles (6400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine Polaris PS-4	_	_	_	N/A	N/A
	interval	50 hour	_	_	_	rafar ta carviac manual	
	capacity		9 oz / 266 mL	_	_	refer to service manual for proper filling	
550 Indy	interval	3.05 quarts / 2.89 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	_	refer to service manual for proper filling	
550 Voyageur	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		20 oz / 592 mL	_	_	refer to service manual for proper filling	
550 Widetrak	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	_	refer to service manual for proper filling	5 quarts / 4.7 liters
600 Indy	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_	_	refer to service manual for proper filling	5.7 quarts / 5.4 liters
600R	interval	3 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL	_	_	refer to service manual for proper filling	4 — 6.3 quarts / 3.8 —6 liters
600/800 Rush, Switchback, Voyageur, RMK	interval	3.9 quarts / 3.7 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 ml	_	_	refer to service manual for proper filling	4 quarts / 3.8 liters
850 AXYS Trail Performance/ Crossover	interval	3.9 quarts / 3.7 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 ml	_	_	refer to service manual for proper filling	5.5 quarts / 5.2 liters
850 AXYS Deep Snow	3.9 quar	3.9 quarts / 3.7 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		_	29 oz / 850 mL	_	refer to service manual for proper filling	8 quarts / 7.6 liters
Titan	interval	3.8 quarts / 3.6 liters	-	500 mile break in, 4000 miles (6400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
	capacity	20 oz(.6L) dry engine Polaris PS-4	_	_	_		
Indy 120	interval	50 hour	_	_	_	N/A	N/A
	capacity		9 oz / 266 mL	_	_	refer to service manual for proper filling	
550 Indy	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	_	refer to service manual for proper filling	
550 Voyageur	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		20 oz / 592 mL	_	_	refer to service manual for proper filling	
550 Widetrak	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	_	refer to service manual for proper filling	5 quarts / 4.7 liters
600 Indy	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		20 oz / 592 mL	_	_	refer to service manual for proper filling	9.8 quarts / 9.3 liters
600 IQ Widetrak	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_	_	refer to service manual for proper filling	5.7 quarts / 5.5 liters
600 Racer	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL	_	_	refer to service manual for proper filling	4 — 6.3 quarts / 3.8 — 6 liters
600/800 Rush, Switchback, Voyageur, RMK	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	_	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		_	29 oz / 850 mL		refer to service manual for proper filling	8 quarts / 7.6 liters
Titan	interval	3.8 quarts / 3.6 liters	-	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine Polaris PS-4	_	_	N/A	N/A
	interval	50 hour	_	_		
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	
550 Indy	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	
550 Voyageur	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	550 Widetrak interval	2.0 quarts / 1.9 liters	20 oz / 592 mL	_	refer to service manual for proper filling	
550 Widetrak			500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	5 quarts / 4.7 liters
600 Indy	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	9.8 quarts / 9.3 liters
600 IQ Widetrak	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL		refer to service manual for proper filling	5.7 quarts / 5.5 liters
600 Racer	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL		refer to service manual for proper filling	4 — 6.3 quarts / 3.8 — 6 liters
600/800 Rush, Switchback, Voyageur, RMK	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine Polaris PS-4	_	_	N/A	N/A
	interval	50 hour	_	_		
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	
550 Indy	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	
550 Voyageur	interval	3.0 quarts / 2.8 liters 5	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	550 Widetrak interval	2.0 quarts / 1.9 liters	20 oz / 592 mL	_	refer to service manual for proper filling	
550 Widetrak			500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	5 quarts / 4.7 Liters
600 / 800 Indy	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	9.8 quarts / 9.3 liters
600 IQ Widetrak	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL		refer to service manual for proper filling	5.7 quarts / 5.5 liters
600 Racer	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL	_	refer to service manual for proper filling	4 – 6.3 quarts / 3.8 – 6 liters
600/800 Rush, Switchback, Voyageur, RMK	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine Polaris PS-4	_		N/A	N/A
	interval	50 hour	_	_		
	capacity		9 oz / 266 mL		refer to service manual for proper filling	
550 Indy	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	
550 Voyageur	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity	2.0 quarts / 1.9 liters	20 oz / 592 mL	_	refer to service manual for proper filling	
550 Widetrak	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	_
600 Indy	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	_
600 IQ Widetrak	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_	refer to service manual for proper filling	_
600 Racer	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL	_	refer to service manual for proper filling	
600/800 Rush, Switchback, Voyageur, RMK	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine *Polaris PS-4	_	_	NI/A	NI/A
may 120	interval	50 hour	_	_	N/A	N/A
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	
550 Indy	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	
550 Voyageur	interval	3.0 quarts / 2.8 liters 5	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters
EDGE / Widetrak	EDGE / Widetrak interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	5 quarts / 4.7 liters
600 Indy	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	7.8 quarts / 7.4 liters
Turbo IQ LXT	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	9.8 quarts / 9.3 liters
600 IQ Widetrak	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz. / 266.2 mL		refer to service manual for proper filling	5.7 quarts / 5.4 liters
600 IQ Racer	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL		refer to service manual for proper filling	5 quarts / 4.7 liters
600/800 Rush, Switchback, Voyageur, RMK	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine *Polaris PS-4	_	_	N/A	N/A
•	interval	50 hour	_	_		
	capacity		20 oz / 592 mL		refer to service manual for proper filling	3.4 quarts / 3.2 liters
EDGE / Widetrak	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	7.8 quarts / 7.4 liters
Turbo IQ LXT	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	20 oz / 592 mL	_	refer to service manual for proper filling	8.9 quarts / 8.4 liters
FS IQ Widetrak	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_	refer to service manual for proper filling	
550 IQ LXT / Shift / Shift 136	interval	3 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		11 oz / 325 mL	_	refer to service manual for proper filling	7 quarts / 6.6 liters
600 IQ LXT	intreval	3.4 quarts / 3.2 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	9.8 quarts / 9.3 liters
600 IQ Widetrak	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz. / 325.3 mL	_	refer to service manual for proper filling	5.3 quarts / 5 liters
600 IQ Racer	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL		refer to service manual for proper filling	5 quarts / 4.7 liters
600/800 Rush, Switchback, Voyageur, RMK	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine *Polaris PS-4	_	_	N/A	N/A
ilidy 120	interval	50 hour	_	_	N/A	N/A
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters
EDGE / Widetrak	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	5 quarts / 4.7 liters
600 Indy	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	7.8 quarts / 7.4 liters LX: 9.6 quarts / 9.1 liters
Turbo IQ / IQ LXT /LX	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	20 oz / 592 mL	_	refer to service manual for proper filling	8.9 quarts / 8.4 liters
FS IQ Widetrak	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_	refer to service manual for proper filling	
550 IQ LXT / Shift / Shift 136	interval	3 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		11 oz / 325 mL	_	refer to service manual for proper filling	7 quarts / 6.6 liters
600 IQ LXT	intreval	3.4 quarts / 3.2 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	9.8 quarts / 9.3 liters
600 IQ Widetrak	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz. / 325.3 mL		refer to service manual for proper filling	5.3 quarts / 5 liters
600 IQ Racer	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL		refer to service manual for proper filling	5 quarts / 4.7 liters
600/800 Rush, Switchback, Voyageur, RMK	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine *Polaris PS-4	_	_	N/A	N/A
	interval	50 hour	_	_		
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters
EDGE / Widetrak	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	7.8 quarts / 7.4 liters LX: 9.6 quarts / 9.1 liters
Turbo IQ / IQ LXT /LX	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	20 oz / 592 mL	_	refer to service manual for proper filling	8.9 quarts / 8.4 liters
FS IQ Widetrak	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_	refer to service manual for proper filling	
550 IQ LXT / Shift / Shift 136	interval	3 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		11 oz / 325 mL	ı	refer to service manual for proper filling	7 quarts / 6.6 liters
600 IQ LXT	intreval	3.4 quarts / 3.2 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	9.8 quarts / 9.3 liters
600 IQ Widetrak	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz. / 325.3 mL	_	refer to service manual for proper filling	5.3 quarts / 5 liters
600 IQ Racer	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL	_	refer to service manual for proper filling	5 quarts / 4.7 liters
600/800 Rush, Switchback, Voyageur, RMK	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

			_		OCK	B L
MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine *Polaris PS-4	_	_	N/A	N/A
·	interval	50 hour	_	_		
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters
Widetrak LX	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	
Trail RMK / Touring	interval	3.4 quarts / 3.2 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	7.8 quarts / 7.4 liters LX: 9.6 quarts / 9.1 liters
FST IQ Touring/ IQ Turbo LX/ Dragon	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	20 oz / 592 mL	_	refer to service manual for proper filling	8.9 quarts / 8.4 liters
FS IQ Widetrak	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_ re	refer to service manual for proper filling	
550 IQ Shift	interval	3 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity		11 oz / 325 mL	_	refer to service manual for proper filling	8.5 quarts / 8 liters
600 IQ LX	intreval	3.4 quarts / 3.2 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	9.8 quarts / 9.3 liters
600 IQ Widetrak	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz. / 325.3 mL		refer to service manual for proper filling	5.3 quarts / 5 liters
600 IQ Racer	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL		refer to service manual for proper filling	5 quarts / 4.7 liters
600 /800 Rush, Switchback, RMK, Dragon	interval	3.8 quarts / 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine *Polaris PS-4	_	_	N/A	N/A
·	interval	50 hour	_	_		·
	capacity		20 oz / 592 mL	-	refer to service manual for proper filling	3.4 quarts / 3.2 liters
Widetrak LX	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	
Trail RMK / Touring / 550 Transport	interval	3.4 quarts / 3.2 liters 5	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	6 – 7 quarts / 6 – 6.6 liters
FST IQ Touring/ IQ Turbo LX/ Dragon / Switchback	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	20 oz / 592 mL	_	refer to service manual for proper filling	8.9 quarts / 8.4 liters
FS IQ Widetrak	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_	refer to service manual for proper filling	550 : N / A 600: 8.5 quarts / 8 liters
550/ 600 IQ Shift	interval	3 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz. / 266 mL	_	refer to service manual for proper filling	10.1 quarts / 9.6 liters
600 IQ RR	interval	2.5 quarts / 2.4 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz. / 325.3 mL	_	refer to service manual for proper filling	5.3 quarts / 5 liters
600 IQ Racer	interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL	1	refer to service manual for proper filling	5 quarts / 4.7 liters
600 /800 Rush, Switchback, RMK, Dragon	interval	3.4 – 3.8 quarts / 3.2 – 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine *Polaris PS-4	_	_	N/A	N/A
	interval	50 hour	_	_		
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters
Widetrak LX	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	N / A 340 : 6.3 quarts / 6 liters
Trail / 550 LX / 340	interval	3.4 quarts / 3.2 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	6 – 7 quarts / 6 – 6.6 liters
FS IQ Widetrak		1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	FST: 3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	6 – 7 quarts / 6 – 6.6 liters
FST / IQ Turbo / Turbo	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz. / 266 mL	_	refer to service manual for proper filling	10.1 quarts / 9.6 liters
600 RR	interval	2.5 quarts / 2.4 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz. / 325.3 mL	_	refer to service manual for proper filling	5.3 quarts / 5 liters
600 IQ Racer interval	3.0 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years	
	capacity		8–10 oz / 237–296 mL	_	refer to service manual for proper filling	5 – 9 quarts / 4.7 – 8.5 liters
IQ Shift / 600 / 700 / 800 Rush, Switchback, RMK, Dragon	interval	3.0 – 3.8 quarts / 2.8 – 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine Polaris PS-4	_		N/A	N/A
ay 120	interval	50 hour	_	_	IV/A	IVA
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters
Widetrak LX	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	3.4 quarts / 3.2 liters	9 oz / 266 mL	_	refer to service manual for proper filling	N / A 340 : 6.3 quarts / 6 liters
Trail / 340 / 500 / 550	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	6– 7 quarts / 6 – 6.6 liters
FS IQ Widetrak	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	6– 7 quarts / 6 – 6.6 liters
FST Classic / Touring / IQ	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz. / 266 mL	1	refer to service manual for proper filling	4 quarts / 3.8 liters
440 Racer	interval	N/A	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL	_	refer to service manual for proper filling	5 – 9 quarts / 4.7 – 8.5 liters
600 / 700 Switchback / RMK / Dragon	interval	3.0 – 3.8 quarts / 2.8 – 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine *Polaris PS-4	_		N/A	N/A
, 120	interval	50 hour	_	_	NA	IN//A
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters
Widetrak LX	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	N / A 340 : 6.3 quarts / 6 liters
Trail / 340 / 500 / 550	interval	3.4 quarts / 3.2 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	6– 7 quarts / 6 – 6.6 liters
FS Classic / Touring	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	_	refer to service manual for proper filling	6– 7 quarts / 6 – 6.6 liters
FST Classic / Touring / Switchback	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz. / 266 mL		refer to service manual for proper filling	4 quarts / 3.8 liters
440 Racer	interval	N/A	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		8–10 oz / 237–296 mL	_	refer to service manual for proper filling	5 – 9 quarts / 4.7 – 8.5 liters
600 / 700 Classic, Dragon	interval	3.0 – 3.8 quarts / 2.8 – 3.6 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
120 XC SP / PRO X	capacity	20 oz(.6L) dry engine Polaris PS-4	_	_	N/A	N/A
120 XO OI / I NO X	interval	50 hour	_	_	14// (
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	5 quarts / 4.7 liters Supersport : N / A
Trail Sport: 500 Indy, Supersport	interval	3.25 quarts / 3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	600, 800: 5.8 quarts / 5.5 liters 340, Trail / DLX: N / A
Touring: 340 Edge, Trail / DLX, 600 Edge, 800 Edge	itersinterval	3.2 quarts / 3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters
Widetrak LX	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		13 oz / 384.5 mL	_	refer to service manual for proper filling	5.5 quarts / 5.2 liters
Frontier Touring	interval	2 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	600 : 5.9 quarts / 5.6 liters N / A
Classic: 340, 500, 550, 600	interval	3.25 quarts / 3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Deep Snow: Trail RMK,	capacity		9 .— 11 oz / 266 — 325 mL		refer to service manual for proper filling	5 – 6.9 quarts / 4.7 – 6.4 liters Trail RMK: N / A
600 / 700 / 800 RMK, 600 / 800 Switchback, 900 RMK	interval	3.25 quarts / 3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 – 11 oz / 266 – 325 mL	_	refer to service manual for proper filling	5.2 – 6.7 quarts / 4.9 – 6.3 liters
Performance: 500 / 600 / 700 / 800 XC SP, 900 Fusion	interval	3 – 3.25 quarts / 2.8 – 3.1 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
120 XC SP / PRO X	capacity	20 oz(.6L) dry engine Polaris PS-4	_	_	NI/A	N/A
120 AC SP / PRO A	interval	50 hour	_	_	N/A	N/A
	capacity		500: 12 oz / 355 mL 9 oz / 266 mL	_	refer to service manual for proper filling	500: 5 quarts / 4.7 liters N / A
Trail Sport: 340 Edge, 500 Edge, Super Sport	interval	3.25 quarts / 3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_	refer to service manual for proper filling	600, 700, 800: 5.8 quarts / 5.5 liters N / A
Touring: 340, Sport, Trail , 600 / 700 / 800 Classic	itersinterval	3.2 quarts / 3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Widetrak LX	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		13 oz / 384.5 mL	_	refer to service manual for proper filling	5.5 quarts / 5.2 liters
Frontier: Touring, Classic	interval	2 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	600, 700, 800: 5.9 quarts / 5.6 liters N / A
Trail Luxury: 340 Edge, 500, 550, 600, 700, 800	interval	3.25 quarts / 3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		11 oz / 325 mL	_	refer to service manual for proper filling	4.3 quarts / 4.1 liters Trail RMK: N / A
Deep Snow: Trail RMK, 600 / 700 / 800 RMK, 600 / 700 / 800 Switchback	interval	3.25 quarts / 3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL 440: N / A		refer to service manual for proper filling	4.5 quarts / 4.2 liters 440, 550 : N / A
Pro: 440 / 550 / 600 / 700 / 800 X, 800 XR	interval	3.25 quarts / 3 liters 440: N / A	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL	_	refer to service manual for proper filling	5.9 quarts / 5.6 liters
Performance: 500 / 600 / 700 / 800 XC SP	interval	3.25 quarts / 3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	
120 XC SP / PRO X	capacity	20 oz(.6L) dry engine Polaris PS-4	_	_	N/A	N/A	
	interval	50 hour		_			
Trail Sport: 340 Edge, 340	capacity	_	500, Super Sport: 11 oz / 325 mL 9 oz / 266 mL	_	refer to service manual for proper filling	500: 4 quarts / 3.8 liters N / A	
Classic, 500 Edge, Super Sport, 440 PRO X FAN	interval	3.25 — 4 quarts / 3 — 3.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years	
Touring: 340, Sport, Trail	capacity		9 – 13 oz / 266 – 384 mL	_	refer to service manual for proper filling	600, 500, 700: 3.8 – 5.8 quarts / 3.6 – 5.5 liters N / A	
, 500 / 600 / 700 / 800 Classic	interval	2 – 4 quarts / 1.9 — 3.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years	
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters	
Widetrak LX		2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years	
	capacity	capacity		12 oz / 325 mL	_	refer to service manual for proper filling	6 quarts / 5.6 liters
Frontier: Touring, Classic	interval	2 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years	
	capacity		11 oz / 325 mL	_	refer to service manual for proper filling	500, 600, 700, 800: 4 quarts / 3.8 liters N / A	
Trail Luxury: 340 Edge, 500, 550, 600, 700, 800	interval	3.25 quarts / 3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years	
	capacity		9 – 11 oz / 266– 325 mL	_	refer to service manual for proper filling	4.7 quarts / 4.5 liters Trail RMK: N / A	
Deep Snow: Trail RMK, 600 / 700 / 800 RMK, 700 / 800 SKS	interval	3 — 4 quarts / 2.8 — 3.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years	
High Porformance: 440	capacity		9 – 11 oz / 266 – 325 mL 440: N / A	_	refer to service manual for proper filling	4.5 quarts / 4.2 liters 440 PRO X FAN: N / A	
High Performance: 440 PRO X FAN, 440 / 600 / 700 / 800 PRO X	interval	3.25 quarts / 3 liters 440 PRO X: N / A	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years	
	capacity	2.05 000-1-10 1000	11 oz / 325 mL 800 XCR: 9 oz / 266 mL		refer to service manual for proper filling	4.7 quarts / 4.5 liters 800 XCR: 7.3 quarts / 6.9 liters	
Performance: 500 / 600 / 700 / 800 XC SP, 800 XCR	interval	3.25 quarts / 3 liters 800 XCR: 2.4 quarts / 2.3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years	

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
120 XC SP / PRO X	capacity	20 oz(.6L) dry engine Polaris PS-4	_	_	N/A	N/A
	interval	50 hour	— 500, Super Sport: 11	_		
	capacity		oz / 325 mL 9 oz / 266 mL	_	refer to service manual for proper filling	500: 4 quarts / 3.8 liters N / A
Trail Sport: 340 Deluxe, Indy 500, Super Sport	interval	3.25 — 4 quarts / 3 — 3.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
T . 11. (T	capacity	2 – 4 quarts / 1.9 — 3.8	9 – 13 oz / 266 – 384 mL	_	refer to service manual for proper filling	600, 500: 3.8 – 5.8 quarts / 3.6 – 5.5 liters N / A
Two-Up / Touring: 340, Sport, Trail , 500 / 600 Classic	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Widetrak LX	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 265 mL	_	refer to service manual for proper filling	3.2 quarts / 3 liters
Frontier	interval	2 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		13 oz / 384 mL	_	refer to service manual for proper filling	4 quarts / 3.8 liters 550: N / A
Trail Luxury: 500, 550, 600, 700	interval	4 quarts / 3.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Deep Snow: Trail RMK,	capacity		9 – 11 oz / 266– 325 mL	_	refer to service manual for proper filling	4.3 – 6 quarts / 4 – 5.7 liters Trail RMK: N / A
500/700 SKS, 500 RMK, 600 / 700 / 800 RMK Edge	interval	3 — 4 quarts / 2.8 — 3.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
High Dorformana 440	capacity		9 – 11 oz / 266 – 325 mL 440: N / A	_	refer to service manual for proper filling	4.5 quarts / 4.2 liters 440 PRO X FAN: N / A
High Performance: 440 PRO X FAN, 440 / 600 PRO X	interval	3.5 quarts / 3.3 liters 440 PRO X: N / A	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Performance: 500 XC,	capacity	A questo / 2 0 liber	11 oz / 325 mL 800 XCR: 9 oz / 266 mL	_	refer to service manual for proper filling	4 quarts / 3.8 liters 800 XCR: 7.3 quarts / 6.9 liters
500 / 600 / 700 / 800 XC SP, 800 XCR	interval	4 quarts / 3.8 liters 800 XCR: 2.4 quarts / 2.3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
120 XC SP / PRO X	capacity	20 oz(.6L) dry engine Polaris PS-4	_	_	N/A	N/A
	interval	50 hour	_	_		
Trail Sport: 340 Deluxe,	capacity		500, Super Sport: 11 oz / 325 mL 9 oz / 266 mL	-	refer to service manual for proper filling	500: 4 quarts / 3.8 liters N / A
Indy 500, Super Sport Edge	interval	2 — 4 quarts / 1.9 — 3.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Two Up / Tourings 240	capacity	2 – 3 quarts / 1.9 — 2.8 liters 5	9 oz / 266 mL	_	refer to service manual for proper filling	600, 500: 3 quarts / 2.8 liters N / A
Two-Up / Touring: 340, Sport / ES, Trail , 500 / 600 Classic	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		20 oz / 592 mL	_	refer to service manual for proper filling	3.4 quarts / 3.2 liters
Widetrak LX	interval	2.0 quarts / 1.9 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	4 quarts / 3.8 liters	13 oz / 384 mL	_	refer to service manual for proper filling	4 quarts / 3.8 liters
Trail Luxury: 500, 600, 700, 800 LE	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Deep Snow: Trail RMK,	capacity		9 – 11 oz / 266– 325 mL	_	refer to service manual for proper filling	5.5 quarts / 5.2 liters Trail RMK: N / A
700 SKS, 500 / 600 / 700 / 800 RMK, 800 RMK Snow-check Special	interval	3 quarts / 2.8 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity		9 oz / 266 mL		refer to service manual for proper filling	4.5 quarts / 4.2 liters 440 XCF SP: N / A
High Performance: 440 XCF SP, 440 / 600 Edge Pro X	interval	3.5 quarts / 3.3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
D. (capacity	4	11 oz / 325 mL 800 XCR: 9 oz / 266 mL	_	refer to service manual for proper filling	4 quarts / 3.8 liters 800 XCR: 7.3 quarts / 6.9 liters
Performance: 500 XC, 500 / 600 / 700 / 800 XC SP, 600 EDGE X, 800 XCR	interval	4 quarts / 3.8 liters 800 XCR: 2.4 quarts / 2.3 liters	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
120 XC SP / PRO X	capacity	20 oz (.6L) dry engine Polaris PS-4 50 hour	_	_	N/A	N/A
	interval		_	_		
Trail Sport: 340 Deluxe, Indy 500, Super Sport	capacity	2 — 3 quarts / 1.9 — 2.8 liters	500, Super Sport: 7 oz / 210 mL 9 oz / 266 mL	_	refer to service manual for proper filling	500: 3 quarts / 2.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Two-Up / Touring: 340, Sport / ES, Trail, 500 Classic, 600, Classic, Triumph	capacity	2 – 3 quarts / 1.9 — 2.8 liters	9 oz / 266 mL Triumph: 7 oz / 210 mL	_	refer to service manual for proper filling	Classic, Triumph, 600, 500: 3 quarts / 2.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Widetrak LX	capacity	2.4 quarts / 2.3 liters	20 oz / 592 mL	_	refer to service manual for proper filling	3 quarts / 2.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	3 quarts / 2.8 liters	7 oz / 210 mL		refer to service manual for proper filling	5.5 quarts / 5.2 liters Trail RMK: N / A
Deep Snow: Trail RMK, 700 SKS, 500 / 600 / 700 / 800 RMK	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
High Performance: 440 XC SP, 440 / 600 Edge Pro X	capacity	3.5 quarts / 3.3 liters	9 oz / 266 mL	-	refer to service manual for proper filling	4 quarts / 3.8 liters 440 XCF SP: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Performance: 500 XC, 500 / 600 / 700 XC SP, 800 XCR, 600 / 700 XC DLX	capacity	3 quarts / 2.8 liters 800 XCR: 2.4 quarts / 2.3 liters	7 oz / 210 mL 600 / 700 XC DLX: 9 oz / 266 mL	_	refer to service manual for proper filling	3 quarts / 2.8 liters 800 XCR: 7.3 quarts / 6.9 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		VES SYNTHETIC 2- CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
340 Deluxe, Indy Sport, Trail, Super Sport, Indy 500, Indy RMK	capacity	2 quarts / 1.9 liters Super Sport: 3 quarts / 2.8 liters	7 oz / 210 mL	_	refer to service manual for proper filling	RMK, 500: 3 quarts / 2.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
340, Indy Sport Touring, Indy Transport, Trail Touring, 500 Classic,	capacity	2 quarts / 1.9 liters	7 oz / 210 mL XLT Touring, XLT Classic, Classic Touring, 500, Trail, Transport: 9 oz / 266 mL	ı	refer to service manual for proper filling	XLT Touring, XLT Classic, XLT Special, Classic Touring, 500: 3 quarts / 2.8 liters N / A
Classic Touring, XLT Special, XLT Classic, XLT Touring	interval	2 quarto / 1.0 more	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	2.4 quarts / 2.3 liters	20 oz / 592 mL	_	refer to service manual for proper filling	3 quarts / 2.8 liters
Widetrak LX	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
	capacity	3 quarts / 2.8 liters	7 oz / 210 mL	_	refer to service manual for proper filling	3 quarts / 2.8 liters Trail RMK: N / A
Trail RMK, Indy 600 / 700 RMK, Indy 700 SKS			500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Indy 700/ 800 XCR	capacity	2.4 quarts / 2.3 liters	7 oz / 210 mL	_	refer to service manual for proper filling	3 quarts / 2.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
XCF, 440 XCR, Indy 500 / 600 / 700 XC / SP	capacity	3 quarts / 2.8 liters	7 oz / 210 mL	_	refer to service manual for proper filling	3 quarts / 2.8 liters XCF: N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

<u>NOTES</u>