

# **POLARIS**

Think Outside

## **Lube Specifications Chart Service Manual**

**Publication Printed 12/18/2023**

© Copyright Polaris Inc. All information contained within this publication is based on the latest product information at the time of publication. Due to constant improvements in the design and quality of production components, some minor discrepancies may result between the actual vehicle and the information presented in this publication. Depictions and/or procedures in this publication are intended for reference use only. No liability can be accepted for omissions or inaccuracies. Any reprinting or reuse of the depictions and/or procedures contained within, whether whole or in part, is expressly prohibited. Printed in U.S.A.

**INDIAN MOTORCYCLE SERVICE PRODUCTS AND LUBRICANTS****MAINTENANCE PRODUCT PART NUMBERS**

<b>PRODUCT</b>		<b>PART NUMBER</b>
All Season Premium Grease	14 oz	2871423
Anti-Freeze, 50/50 Extended Life (Scout)	1 quart (32 oz)	2880966
Brake Fluid, DOT 4	12 oz	2880016
Carbon Cleaner, Fuel	12 oz	2881911
Crankcase Sealant (Loctite Ultra Black 598)		Commercially Available
Fork Oil	quart	2208093
Chain Lube	11 oz	2884172
Oil Change Kit (Thunder Stroke Engines)	20W-40	2880067
Oil Change Kit (Scout/Thunder Stroke Engines)	15W-60	2880191
Oil Change Kit (Challenger Engines)	15W-60	2884171
Oil Change Kit (FTR Engines)	15W-60	2884182
Synthetic 15W-60 Engine Lubricant (Scout/Thunder Stroke/Challenger Engines)	quart	2880187
	55 gal drum	2880188
Semi-Synthetic 20W-40 Engine Lubricant (Thunder Stroke Engines)	quart	2880012
	55 gal drum	2880013

# CHAPTER 4

## INDIAN MOTORCYCLE LUBE CHART

INDIAN MOTORCYCLE LUBE CHART 2024 .....	4.2
INDIAN MOTORCYCLE LUBE CHART 2023 .....	4.3
INDIAN MOTORCYCLE LUBE CHART 2022 .....	4.4
INDIAN MOTORCYCLE LUBE CHART 2021 .....	4.5
INDIAN MOTORCYCLE LUBE CHART 2020 .....	4.6
INDIAN MOTORCYCLE LUBE CHART 2019 .....	4.7
INDIAN MOTORCYCLE LUBE CHART 2018 .....	4.8
INDIAN MOTORCYCLE LUBE CHART 2017 .....	4.8
INDIAN MOTORCYCLE LUBE CHART 2016 .....	4.9
INDIAN MOTORCYCLE LUBE CHART 2015 .....	4.9
INDIAN MOTORCYCLE LUBE CHART 2014 .....	4.10
INDIAN MOTORCYCLE LUBE CHART 2013 .....	4.10
INDIAN MOTORCYCLE LUBE CHART 2012 .....	4.10
INDIAN MOTORCYCLE LUBE CHART 2011 .....	4.11
INDIAN MOTORCYCLE LUBE CHART 2010 .....	4.11
INDIAN MOTORCYCLE LUBE CHART 2009 .....	4.11

**INDIAN MOTORCYCLE LUBE CHART 2024**

MODEL		ENGINE OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 PRE-MIXED EXTENDED LIFE ANTI- FREEZE	OIL FILTER	OIL CHANGE KIT
<b>Roadmaster / Chieftain / Springfield (Thunderstroke 111 and 116)</b>	capacity	<b>6.0 qt (5.7 L) with filter at oil change 20W-40</b>	—	<b>18.8 oz557 cm<sup>3</sup></b> Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			
<b>Scout / Scout Sixty</b>	capacity	<b>3-4 qt (2.8-3.8 L) with filter at oil change 15W-60</b>	—	<b>10.65 oz315 cm<sup>3</sup> 18.6 oz550 cm<sup>3</sup></b> Refer to front fork assembly section in service manual for proper filling and fluid level	<b>2.75 qt (2.6 L)</b>	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Scout Bobber</b>	capacity	<b>3-4 qt (2.8-3.8 L) with filter at oil change 15W-60</b>	—	Left-Hand (PN: 1824582): <b>277 cc</b> Right-Hand (PN: 1824583): <b>273 cc</b> Refer to front fork assembly section in service manual for proper filling and fluid level	<b>2.75 qt (2.6 L)</b>	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Challenger / Pursuit</b>	capacity	<b>5.0 qt (4.7 L) with filter at oil change 15W-60</b>	—	<b>16.4 oz (485 cc) per leg</b> Refer to front fork assembly section in service manual for proper filling and fluid level	<b>2.4 qt (2.3 L)</b>	2521421	2884171
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>FTR 1200</b>	capacity	<b>4.5 qt (4.25 L) with filter at oil change 15W-60</b>	—	<b>17.2 ± .2 oz508 ± 6 cm<sup>3</sup> 17.5 ± .2 oz519 ± 6 cm<sup>3</sup></b>	<b>2.32 qt (2.2 L)</b>	2540086	2884182
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Chief / Chief Bobber / Super Chief</b>	capacity	<b>6.0 qt (5.71 L) with filter at oil change 20W-40</b>	—	<b>550 cc</b> Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521412	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 10000 miles (16000 km)			

INDIAN MOTORCYCLE LUBE CHART 2023

MODEL		ENGINE OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 PRE-MIXED EXTENDED LIFE ANTI- FREEZE	OIL FILTER	OIL CHANGE KIT
<b>Roadmaster / Chieftain / Springfield (Thunderstroke 111 and 116)</b>	capacity	<b>6.0 qt (5.7 L) with filter at oil change 20W-40</b>	—	<b>18.8 oz557 cm<sup>3</sup></b> Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			
<b>Scout / Scout Sixty</b>	capacity	<b>3-4 qt (2.8-3.8 L) with filter at oil change 15W-60</b>	—	<b>10.65 oz315 cm<sup>3</sup> 18.6 oz550 cm<sup>3</sup></b> Refer to front fork assembly section in service manual for proper filling and fluid level	<b>2.75 qt (2.6 L)</b>	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Scout Bobber</b>	capacity	<b>3-4 qt (2.8-3.8 L) with filter at oil change 15W-60</b>	—	Left-Hand (PN: 1824582): <b>277 cc</b>  Right-Hand (PN: 1824583): <b>273 cc</b>  Refer to front fork assembly section in service manual for proper filling and fluid level	<b>2.75 qt (2.6 L)</b>	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Challenger / Pursuit</b>	capacity	<b>5.0 qt (4.7 L) with filter at oil change 15W-60</b>	—	<b>16.4 oz (485 cc) per leg</b> Refer to front fork assembly section in service manual for proper filling and fluid level	<b>2.4 qt (2.3 L)</b>	2521421	2884171
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>FTR 1200</b>	capacity	<b>4.5 qt (4.25 L) with filter at oil change 15W-60</b>	—	<b>17.2 ± .2 oz508 ± 6 cm<sup>3</sup> 17.5 ± .2 oz519 ± 6 cm<sup>3</sup></b>	<b>2.32 qt (2.2 L)</b>	2540086	2884182
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Chief / Chief Bobber / Super Chief</b>	capacity	<b>6.0 qt (5.71 L) with filter at oil change 20W-40</b>	—	<b>550 cc</b> Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521412	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 10000 miles (16000 km)			

**INDIAN MOTORCYCLE LUBE CHART 2022**

MODEL		ENGINE OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 PRE-MIXED EXTENDED LIFE ANTI- FREEZE	OIL FILTER	OIL CHANGE KIT
<b>Roadmaster / Chieftain / Springfield (Thunderstroke 111 and 116)</b>	capacity	6.0 qt (5.7 L) with filter at oil change 20W-40	—	*18.8 oz (557 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			
<b>Scout / Scout Sixty</b>	capacity	3-4 qts. (2.8-3.8 L) with filter at oil change 15W-60	—	10.65 oz. (315 cc) 18.6 oz. (550 cc) Refer to front fork assembly section in service manual for proper filling and fluid level	2.75 qts. (2.6 L)	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Scout Bobber</b>	capacity	3-4 qts. (2.8-3.8 L) with filter at oil change 15W-60	—	277CC left leg 273CC right leg Refer to front fork assembly section in service manual for proper filling and fluid level	2.75 qts. (2.6 L)	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Challenger / Pursuit</b>	capacity	5.0 qt (4.7 L) dry engine 15W-60	—	16.4 oz (485 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	2.4 qt (2.3 L)	2521421	2884171
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>FTR 1200</b>	capacity	4.5 qts. (4.25 L) Dry Engine 15W-60	—	Rally 519 +/- 6cc FTRS 508 cc +/- 6cc FTR R carbon 544 cc +/- 6cc	2.32 qts. (2.2 L)	2540086	2884182
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Chief / Chief Bobber / Super Chief</b>	capacity	6.0 qts. (5.7 l) with filter at oil change 20W-40	—	550 cc 18.6 oz Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521412	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 10000 miles (16000 km)			

**INDIAN MOTORCYCLE LUBE CHART 2021**

MODEL		ENGINE OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 PRE-MIXED EXTENDED LIFE ANTI- FREEZE	OIL FILTER	OIL CHANGE KIT
<b>Roadmaster / Chieftain / Springfield (Thunderstroke 111 and 116)</b>	capacity	6.0 qt (5.7 L) with filter at oil change 20W-40	—	*20.3 oz (599 cc) per leg (Chief, Classic, Vintage, Chieftain / Darkhorse) *18.8 oz (557 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			
<b>Scout / Scout Sixty</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	*10.65 oz (315 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	2.93 qt (2.78 L) including recovery bottle	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Scout Bobber</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	*Left-Hand: 9.37 oz (277 cc) Right-Hand: 9.23 oz (273 cc) Refer to front fork assembly section in service manual for proper filling and fluid level	2.93 qt (2.78 L) including recovery bottle	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Challenger</b>	capacity	5.0 qt (4.7 L) dry engine 15W-60	—	16.4 oz (485 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	2.4 qt (2.3 L)	2521421	2884171
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		

4

**INDIAN MOTORCYCLE LUBE CHART 2020**

MODEL		ENGINE OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 PRE-MIXED EXTENDED LIFE ANTI- FREEZE	OIL FILTER	OIL CHANGE KIT
<b>Roadmaster / Chieftain / Springfield (Thunderstroke 111 and 116)</b>	capacity	Refer to Team Tip I-19- 09-01 20W-40	—	*20.3 oz (599 cc) per leg (Chief, Classic, Vintage, Chieftain / Darkhorse) *18.8 oz (557 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			
<b>Scout / Scout Sixty</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	*10.65 oz (315 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	2.93 qt (2.78 L) including recovery bottle	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Scout Bobber</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	*Left-Hand: 9.37 oz (277 cc) Right-Hand: 9.23 oz (273 cc) Refer to front fork assembly section in service manual for proper filling and fluid level	2.93 qt (2.78 L) including recovery bottle	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Challenger</b>	capacity	5.0 qt (4.7 L) dry engine 15W-60	—	16.4 oz (485 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	2.4 qt (2.3 L)	2521421	2884171
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>FTR</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	1200: 17.5 oz (519 cc) 1200S: 17.2 oz (508 cc) Refer to front fork assembly section in service manual for proper filling and fluid level	2.32 qt (2.2 L)	2540086	2884182
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		



**INDIAN MOTORCYCLE LUBE CHART 2019**

MODEL		ENGINE OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 PRE-MIXED EXTENDED LIFE ANTI- FREEZE	OIL FILTER	OIL CHANGE KIT
<b>Roadmaster / Chieftain / Springfield (Thunderstroke 111)</b>	capacity	Refer to Team Tip I-19-09-01 20W-40	—	*20.3 oz (599 cc) per leg (Chief, Classic, Vintage, Chieftain / Darkhorse) *18.8 oz (557 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			
<b>Scout / Scout Sixty</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	*10.65 oz (315 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	2.93 qt (2.78 L) including recovery bottle	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Scout Bobber</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	*Left-Hand: 9.37 oz (277 cc) Right-Hand: 9.23 oz (273 cc) Refer to front fork assembly section in service manual for proper filling and fluid level	2.93 qt (2.78 L) including recovery bottle	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>FTR</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	1200: 17.5 oz (519 cc) 1200S: 17.2 oz (508 cc) Refer to front fork assembly section in service manual for proper filling and fluid level	2.32 qt (2.2 L)	2540086	2884182
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		

4

**INDIAN MOTORCYCLE LUBE CHART 2018**

MODEL		ENGINE OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
<b>Roadmaster / Chieftain / Springfield (Thunderstroke 111)</b>	capacity	Refer to Team Tip I-19-09-01 20W-40	—	*20.3 oz (599 cc) per leg (Chief, Classic, Vintage, Chieftain / Darkhorse) *18.8 oz (557 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			
<b>Scout / Scout Sixty</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	*10.65 oz (315 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	2.93 qt (2.78 L) including recovery bottle	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		
<b>Scout Bobber</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	*Left-Hand: 9.37 oz (277 cc) Right-Hand: 9.23 oz (273 cc) Refer to front fork assembly section in service manual for proper filling and fluid level	2.93 qt (2.78 L) including recovery bottle	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		

**INDIAN MOTORCYCLE LUBE CHART 2017**

MODEL		ENGINE OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
<b>Roadmaster / Chieftain / Springfield (Thunderstroke 111)</b>	capacity	Refer to Team Tip I-19-09-01 20W-40	—	*20.3 oz (599 cc) per leg (Chief, Classic, Vintage, Chieftain / Darkhorse) *18.8 oz (557 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			
<b>Scout / Scout Sixty</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	*11.2 oz (335 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	2.93 qt (2.78 L) including recovery bottle	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		

**INDIAN MOTORCYCLE LUBE CHART 2016**

MODEL		ENGINE OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
<b>Roadmaster / Chieftain / Springfield (Thunderstroke 111)</b>	capacity	Refer to Team Tip I-19-09-01 20W-40	—	*20.3 oz (599 cc) per leg (Chief, Classic, Vintage, Chieftan / Darkhorse) *18.8 oz (557 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			
<b>Scout / Scout Sixty</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	*11.2 oz (335 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	2.93 qt (2.78 L) including recovery bottle	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		

4

**INDIAN MOTORCYCLE LUBE CHART 2015**

MODEL		ENGINE OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
<b>Roadmaster / Chieftain (Thunderstroke 111)</b>	capacity	Refer to Team Tip I-19-09-01 20W-40	—	*20.3 oz (599 cc) per leg (Chief, Classic, Vintage, Chieftan / Darkhorse) *18.8 oz (557 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			
<b>Scout / Scout Sixty</b>	capacity	4.5 qt (4.25 L) dry engine 15W-60	—	*11.2 oz (335 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	2.93 qt (2.78 L) including recovery bottle	2520799	2880191
	interval	10000 miles (16000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)	5 years / 50000 miles (80000 km)		

**INDIAN MOTORCYCLE LUBE CHART 2014**

MODEL		ENGINE OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
Chief / Chieftain	capacity	Refer to Team Tip I-19-09-01 20W-40	—	Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			

**INDIAN MOTORCYCLE LUBE CHART 2013**

MODEL		ENGINE OIL	TRANSMISSION OIL SYNTHETIC 80W90 GEAR OIL	PRIMARY DRIVE OIL SYNTHETIC 80W90 GEAR OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
Chief	capacity	3.5 qt (3.31 L) with filter at oil change 20W-40	20–24 oz (600–720 cc)	20–22 oz (591–650 cc)	—	*11 oz (325 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	5000 miles (8000 km)	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			

**INDIAN MOTORCYCLE LUBE CHART 2012**

MODEL		ENGINE OIL	TRANSMISSION OIL SYNTHETIC 80W90 GEAR OIL	PRIMARY DRIVE OIL SYNTHETIC 80W90 GEAR OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
Chief	capacity	3.5 qt (3.31 L) with filter at oil change 20W-40	20–24 oz (600–720 cc)	20–22 oz (591–650 cc)	—	*11 oz (325 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	5000 miles (8000 km)	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			

**INDIAN MOTORCYCLE LUBE CHART 2011**

MODEL		ENGINE OIL	TRANSMISSION OIL SYNTHETIC 80W90 GEAR OIL	PRIMARY DRIVE OIL SYNTHETIC 80W90 GEAR OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
Chief	capacity	3.5 qt (3.31 L) with filter at oil change 20W-40	20–24 oz (600–720 cc)	20–22 oz (591–650 cc)	—	*10.5 oz (310 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	5000 miles (8000 km)	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			

4

**INDIAN MOTORCYCLE LUBE CHART 2010**

MODEL		ENGINE OIL	TRANSMISSION OIL SYNTHETIC 80W90 GEAR OIL	PRIMARY DRIVE OIL SYNTHETIC 80W90 GEAR OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
Chief	capacity	3.5 qt (3.31 L) with filter at oil change 20W-40	20–24 oz (600–720 cc)	20–22 oz (591–650 cc)	—	*10.5 oz (310 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	5000 miles (8000 km)	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			

**INDIAN MOTORCYCLE LUBE CHART 2009**

MODEL		ENGINE OIL	TRANSMISSION OIL SYNTHETIC 80W90 GEAR OIL	PRIMARY DRIVE OIL SYNTHETIC 80W90 GEAR OIL	BRAKE FLUID DOT 4 BRAKE FLUID	FRONT FORK OIL FORK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
Chief	capacity	3.5 qt (3.31 L) with filter at oil change 20W-40	20–24 oz (600–720 cc)	20–22 oz (591–650 cc)	—	*10.5 oz (310 cc) per leg Refer to front fork assembly section in service manual for proper filling and fluid level	N/A	2521421	2889311
	interval	5000 miles (8000 km)	5000 miles (8000 km)	5000 miles (8000 km)	2 years / 10000 miles (16000 km)	2 years / 15000 miles (24000 km)			

