



Lube Specifications Chart Service Manual

Publication Printed 12/18/2023

© Copyright Polaris Inc. All information contained within this publication is based on the latest product information at the time of publication. Due to constant improvements in the design and quality of production components, some minor discrepancies may result between the actual vehicle and the information presented in this publication. Depictions and/or procedures in this publication are intended for reference use only. No liability can be accepted for omissions or inaccuracies. Any reprinting or reuse of the depictions and/or procedures contained within, whether whole or in part, is expressly prohibited. Printed in U.S.A.

SNOWMOBILE SERVICE PRODUCTS AND LUBRICANTS**MAINTENANCE PRODUCT PART NUMBERS**

PRODUCT		PART NUMBER
VES Synthetic 2-Cycle Oil	Quart	2877882
	Gallon	2877883
	2.5 Gallon	2877884
	16 Gallon	2877885
	55 Gallon	2877886
	330 Gallon	2877892
VES Extreme Synthetic 2-Cycle Oil	Quart	2883733
	Gallon	2883732
	16 Gallon	2883734
	55 Gallon	2883735
	330 Gallon	2883736
Polaris Blue Synthetic Blend 2-Cycle Oil	Quart	2882201
	Gallon	2882202
	16 Gallon	2882203
	55 Gallon	2882205
	330 Gallon	2882206
Vintage 2-Stroke Snowmobile Engine Oil	Quart	2889400
PS-4 Engine Oil (4 stroke)	Quart	2876244
	Gallon	2876245
	16 Gallon	2876247
	Drum (55 Gallon)	2876246
	Tote (330 Gallon)	2878814
Synthetic Chaincase Lubricant	Quart	2873105
	Gallon	2873106
	2.5 Gallon	2872952
50/50 Extended Life Antifreeze	Quart	2880514
	Gallon	2880513
	55 Gallon	2880512
Shock Oil - 5W - Walker Evans	Quart	2874522
Shock Oil - 5W - Fox	Quart	2870995
	2.5 Gallon	2872279
Brake Fluid - DOT 4	12 oz	2872189
Fogging Oil (Aerosol)	12 oz	2870791
Premium All Season Grease	3 oz. Grease Gun Kit	2871312
	14 oz. Tube	2871423
Carbon Clean	12 oz	2881413
Fuel Stabilizer	12 oz	2881416
Three Bond Sealant	5 oz	2871557

CHAPTER 3

SNOWMOBILE LUBE CHART

SNOWMOBILE LUBE CHART 2024.....	3.2
SNOWMOBILE LUBE CHART 2023.....	3.4
SNOWMOBILE LUBE CHART 2022.....	3.6
SNOWMOBILE LUBE CHART 2021.....	3.7
SNOWMOBILE LUBE CHART 2020.....	3.9
SNOWMOBILE LUBE CHART 2019.....	3.10
SNOWMOBILE LUBE CHART 2018.....	3.11
SNOWMOBILE LUBE CHART 2017.....	3.12
SNOWMOBILE LUBE CHART 2016.....	3.13
SNOWMOBILE LUBE CHART 2015.....	3.14
SNOWMOBILE LUBE CHART 2014.....	3.15
SNOWMOBILE LUBE CHART 2013.....	3.16
SNOWMOBILE LUBE CHART 2012.....	3.17
SNOWMOBILE LUBE CHART 2011.....	3.18
SNOWMOBILE LUBE CHART 2010.....	3.19
SNOWMOBILE LUBE CHART 2009.....	3.20
SNOWMOBILE LUBE CHART 2008.....	3.21
SNOWMOBILE LUBE CHART 2007.....	3.22
SNOWMOBILE LUBE CHART 2006.....	3.23
SNOWMOBILE LUBE CHART 2005.....	3.24
SNOWMOBILE LUBE CHART 2004.....	3.25
SNOWMOBILE LUBE CHART 2003.....	3.26
SNOWMOBILE LUBE CHART 2002.....	3.27
SNOWMOBILE LUBE CHART 2001.....	3.28
SNOWMOBILE LUBE CHART 2000.....	3.29
SNOWMOBILE LUBE CHART 1999.....	3.30

SNOWMOBILE LUBE CHART 2024

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
550 PRO-RIDE	capacity	3.05 qt (2.89 L) Polaris Blue Synthetic Blend 2- Cycle Oil	8.96 oz (265 mL)	—	—	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)		
600R	capacity	N/A VES Extreme Synthetic 2-Cycle Oil	—	—	—	Refer to service manual for proper filling	5.7 qt (5.4 L)
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 Matryx Indy Cross Country	capacity	3.75 qt (3.5 L) VES Extreme Synthetic 2-Cycle Oil	8 - 10 oz (237 - 296 mL)	—	—	Refer to service manual for proper filling	6.4 qt (6.06 L)
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
650/850 Matryx Trail Performance/ Crossover	capacity	3.75 qt (3.5 L) VES Synthetic 2- Cycle Oil	8 - 10 oz (237 - 296 mL)	—	—	Refer to service manual for proper filling	129: 6.25 qt (5.92 L) 137: 6.47 qt (6.13 L) 146: 6.67 qt (6.31 L)
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
650/850 Matryx Long Track	capacity	3.9 qt (3.7 L) VES Synthetic 2- Cycle Oil	—	—	—	Refer to service manual for proper filling	Slash: 5.34 qt (5.05 L) Standard: 6.16 qt (5.83 L)
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
850 Matryx Boost Long Track	capacity	3.9 qt (3.7 L) VES Extreme Synthetic 2-Cycle Oil	—	—	—	Refer to service manual for proper filling	5.4 qt (5.12 L)
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
9R Matryx Long Track	capacity	3.9 qt (3.7 L) VES Extreme Synthetic 2-Cycle Oil	—	—	—	Refer to service manual for proper filling	146: 6.16 qt (5.83 L) 155: 5.34 qt (5.05 L) 163/165: 5.34 qt (5.05 L)
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		PS-4 EXTREME 0W-50 FULL SYNTHETIC ENGINE OIL 2889395	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
ProStar S4 Titan	capacity	3.7 qt (3.5 L)	—	24 oz (710 mL)	—	Refer to service manual for proper filling	8 qt (7.6 L)	2522606	
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years		
Prostar S4 Trail Performance / Recreation	capacity	3.7 qt (3.5 L)	—	23.6 oz (700 mL)	—	Refer to service manual for proper filling		2522606	
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years		

SNOWMOBILE LUBE CHART 2023

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz (.6 L) of Polaris PS-4	—	—	—	N/A	N/A
	interval	50 hour	—	—	—		
550 PRO-RIDE	capacity	3.05 qt (2.89 L) Polaris Blue Synthetic Blend 2- Cycle Oil	8.96 oz (265 mL)	—	—	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)		
600R	capacity	N/A VES Extreme Synthetic 2-Cycle Oil	—	—	—	Refer to service manual for proper filling	5.7 qt (5.4 L)
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
800 Titan	capacity	3.8 qt (3.6 L) VES Synthetic 2- Cycle Oil	—	29 oz (850 L)	—	Refer to service manual for proper filling	8 qt (7.6 L)
	interval		—	4000 miles (6400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 Matryx Indy Cross Country	capacity	3.75 qt (3.5 L) VES Extreme Synthetic 2-Cycle Oil	8 - 10 oz (237 - 296 mL)	—	—	Refer to service manual for proper filling	6.4 qt (6.06 L)
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
650/850 Matryx Trail Performance/ Crossover	capacity	3.75 qt (3.5 L) VES Synthetic 2- Cycle Oil	8 - 10 oz (237 - 296 mL)	—	—	Refer to service manual for proper filling	129: 6.25 qt (5.92 L) 137: 6.47 qt (6.13 L) 146: 6.67 qt (6.31 L)
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
650/850 Matryx Long Track	capacity	3.9 qt (3.7 L) VES Synthetic 2- Cycle Oil	—	—	—	Refer to service manual for proper filling	Slash: 5.34 qt (5.05 L) Standard: 6.16 qt (5.83 L)
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
850 Matryx Boost Long Track	capacity	3.9 qt (3.7 L) VES Extreme Synthetic 2-Cycle Oil	—	—	—	Refer to service manual for proper filling	5.4 qt (5.12 L)
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
9R Matryx Long Track	capacity	3.9 qt (3.7 L) VES Extreme Synthetic 2-Cycle Oil	—	—	—	Refer to service manual for proper filling	146: 6.16 qt (5.83 L) 155: 5.34 qt (5.05 L) 163/165: 5.34 qt (5.05 L)
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

MODEL		PS-4 EXTREME 0W-50 FULL SYNTHETIC ENGINE OIL 2889395	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE	OIL FILTER	OIL CHANGE KIT
ProStar S4 Titan	capacity	3.7 qt (3.5 L)	—	24 oz (710 mL)	—	Refer to service manual for proper filling	8 qt (7.6 L)	2522606	
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years		
Prostar S4 Trail Performance / Recreation	capacity	3.7 qt (3.5 L)	—	23.6 oz (700 mL)	—	Refer to service manual for proper filling		2522606	
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years		

SNOWMOBILE LUBE CHART 2022

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz (6L) dry engine Polaris PS-4	—	—	—	N/A	N/A
	interval	50 hour	—	—	—		
550 PRO-RIDE	capacity	3.05 quarts / 2.89 liters Polaris Blue Synthetic Blend 2- Cycle Oil	8.96 oz / 265 mL	—	—	High performance shocks should have oil changed and recharged at the end of every riding season.	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)		
600R	capacity	N/A VES Extreme Synthetic 2-Cycle Oil	11 oz / 325.3 ml	—	—	refer to service manual for proper filling	5.7 quarts / 5.4 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 AXYS Trail Performance/ Crossover	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 ml	—	—	refer to service manual for proper filling	4 quarts / 3.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
850 AXYS Deep Snow	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	—	—	—	refer to service manual for proper filling	5.3 - 5.5 quarts / 5 - 5.3 liters
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Titan 800	capacity	3.8 quarts / 3.6 liters VES Synthetic 2- Cycle Oil	—	29 oz / 850 mL	—	refer to service manual for proper filling	8 quarts / 7.6 liters
	interval		—	4000 miles (6400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 Matryx Indy Cross Country	capacity	3.75 quarts / 3.5 liters VES Extreme Synthetic 2-Cycle Oil	8-10 oz / 237-296 mL	—	—	refer to service manual for proper filling	4 quarts / 3.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
650/850 Matryx Trail Performance/ Crossover	capacity	3.75 quarts / 3.5 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 ml	—	—	refer to service manual for proper filling	4 quarts / 3.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
650/850 Matryx Deep Snow	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	—	—	—	refer to service manual for proper filling	Slash Models - 5.6 quarts / 5.3 liters Standard Models - 6.25 quarts / 6.05 liters
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Matryx Boost Deep Snow	capacity	3.9 quarts / 3.7 liters VES Extreme Synthetic 2-Cycle Oil	—	—	—	refer to service manual for proper filling	5.6 quarts / 5.3 liters
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2021

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz.(6L) dry engine Polaris PS-4	—	—	—	N/A	N/A
	interval	50 hour	—	—	—		
550 Indy	capacity	3.05 quarts / 2.89 liters Polaris Blue Synthetic Blend 2- Cycle Oil	9oz / 266 mL	—	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Voyager	capacity	3.05 quarts / 2.89 liters Polaris Blue Synthetic Blend 2- Cycle Oil	9oz / 266 mL	—	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
600 Indy	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	10 oz / 296 mL	—	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600R	capacity	3 quarts / 2.8 liters VES Extreme Synthetic 2-Cycle Oil	11 oz / 325 mL	—	—	refer to service manual for proper filling	5.7 quarts / 5.4 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 AXYS Trail Performance/ Crossover	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 mL	—	—	refer to service manual for proper filling	4 quarts / 3.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
850 AXYS Trail Performance/ Crossover	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 ml	—	—	refer to service manual for proper filling	4 quarts / 3.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 AXYS Deep Snow	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	—	—	—	refer to service manual for proper filling	5.3 quarts / 5 liters
	interval		—	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
850 AXYS Deep Snow	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 ml (If Equipped)	—	—	refer to service manual for proper filling	5.3 - 5.7 quarts / 5 - 5.4 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
650/850 Matryx Trail Performance	capacity	3.75 quarts / 3.5 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 ml	—	—	refer to service manual for proper filling	4 quarts / 3.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Titan	capacity	3.8 quarts / 3.6 liters VES Synthetic 2- Cycle Oil	—	28 oz / 828 mL	—	refer to service manual for proper filling	8 quarts / 7.6 liters

SNOWMOBILE LUBE CHART 2020

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine Polaris PS-4	—	—	—	N/A	N/A
	interval	50 hour	—	—	—		
550 Indy	capacity	3.05 quarts / 2.89 liters Polaris Blue Synthetic Blend 2- Cycle Oil	9 oz / 266 mL	—	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Voyager	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2- Cycle Oil	9 oz / 266 mL	—	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Widetrak	capacity	2.0 quarts / 1.9 liters Polaris Blue Synthetic Blend 2- Cycle Oil	20 oz / 592 mL	—	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
600 Indy	capacity	3.8 quarts / 3.6 liters VES Synthetic 2- Cycle Oil	9 oz / 266 mL	—	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600R	capacity	3 quarts / 2.8 liters VES Extreme Synthetic 2-Cycle Oil	11 oz / 325 mL	—	—	refer to service manual for proper filling	5.7 quarts / 5.4 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600/800 Rush, Switchback, Voyageur, RMK	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 mL	—	—	refer to service manual for proper filling	4 — 6.3 quarts / 3.8 — 6 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
850 AXYS Trail Performance/ Crossover	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 ml	—	—	refer to service manual for proper filling	4 quarts / 3.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
850 AXYS Deep Snow	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 ml	—	—	refer to service manual for proper filling	5.5 quarts / 5.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Titan	capacity	3.8 quarts / 3.6 liters VES Synthetic 2- Cycle Oil	—	29 oz / 850 mL	—	refer to service manual for proper filling	8 quarts / 7.6 liters
	interval		—	500 mile break in, 4000 miles (6400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2019

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz (6L) dry engine Polaris PS-4	—	—	—	N/A	N/A
	interval	50 hour	—	—	—		
550 Indy	capacity	3.05 quarts / 2.89 liters Polaris Blue Synthetic Blend 2- Cycle Oil	9 oz / 266 mL	—	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Voyageur	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2- Cycle Oil	9 oz / 266 mL	—	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Widetrak	capacity	2.0 quarts / 1.9 liters Polaris Blue Synthetic Blend 2- Cycle Oil	20 oz / 592 mL	—	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
600 Indy	capacity	3.8 quarts / 3.6 liters VES Synthetic 2- Cycle Oil	9 oz / 266 mL	—	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600R	capacity	3 quarts / 2.8 liters VES Extreme Synthetic 2-Cycle Oil	11 oz / 325 mL	—	—	refer to service manual for proper filling	5.7 quarts / 5.4 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600/800 Rush, Switchback, Voyageur, RMK	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 mL	—	—	refer to service manual for proper filling	4 — 6.3 quarts / 3.8 — 6 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
850 AXYS Trail Performance/ Crossover	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 ml	—	—	refer to service manual for proper filling	4 quarts / 3.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
850 AXYS Deep Snow	capacity	3.9 quarts / 3.7 liters VES Synthetic 2- Cycle Oil	8-10 oz / 237-296 ml	—	—	refer to service manual for proper filling	5.5 quarts / 5.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Titan	capacity	3.8 quarts / 3.6 liters VES Synthetic 2- Cycle Oil	—	29 oz / 850 mL	—	refer to service manual for proper filling	8 quarts / 7.6 liters
	interval		500 mile break in, 4000 miles (6400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2018

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	TRANSMISSION OIL AGL	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz.(6L) dry engine Polaris PS-4	—	—	—	N/A	N/A
	interval	50 hour	—	—	—		
550 Indy	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2– Cycle Oil	9 oz / 266 mL	—	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Voyager	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2– Cycle Oil	9 oz / 266 mL	—	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Widetrak	capacity	2.0 quarts / 1.9 liters Polaris Blue Synthetic Blend 2– Cycle Oil	20 oz / 592 mL	—	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
600 Indy	capacity	3.8 quarts / 3.6 liters VES Synthetic 2– Cycle Oil	9 oz / 266 mL	—	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Widetrak	capacity	3.0 quarts / 2.8 liters VES Synthetic 2– Cycle Oil	20 oz / 592 mL	—	—	refer to service manual for proper filling	9.8 quarts / 9.3 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 Racer	capacity	3.0 quarts / 2.8 liters VES Extreme Synthetic 2–Cycle Oil	11 oz / 325 mL	—	—	refer to service manual for proper filling	5.7 quarts / 5.5 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600/800 Rush, Switchback, Voyageur, RMK	capacity	3.8 quarts / 3.6 liters VES Synthetic 2– Cycle Oil	8–10 oz / 237–296 mL	—	—	refer to service manual for proper filling	4 — 6.3 quarts / 3.8 — 6 liters
	interval		500 mile break in, 1500 miles (2400 km)	—	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Titan	capacity	3.8 quarts / 3.6 liters VES Synthetic 2– Cycle Oil	—	29 oz / 850 mL	—	refer to service manual for proper filling	8 quarts / 7.6 liters
	interval		—	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2017

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
550 Indy	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Voyager	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Widetrak	capacity	2.0 quarts / 1.9 liters Polaris Blue Synthetic Blend 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
600 Indy	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Widetrak	capacity	3.0 quarts / 2.8 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	9.8 quarts / 9.3 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 Racer	capacity	3.0 quarts / 2.8 liters VES Extreme Synthetic 2-Cycle Oil	11 oz / 325 mL	—	refer to service manual for proper filling	5.7 quarts / 5.5 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600/800 Rush, Switchback, Voyager, RMK	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	8–10 oz / 237–296 mL	—	refer to service manual for proper filling	4 — 6.3 quarts / 3.8 — 6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2016

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz.(6L) dry engine Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
550 Indy	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Voyageur	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Widetrak	capacity	2.0 quarts / 1.9 liters Polaris Blue Synthetic Blend 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
600 / 800 Indy	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	5 quarts / 4.7 Liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Widetrak	capacity	3.0 quarts / 2.8 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	9.8 quarts / 9.3 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 Racer	capacity	3.0 quarts / 2.8 liters VES Extreme Synthetic 2-Cycle Oil	11 oz / 325 mL	—	refer to service manual for proper filling	5.7 quarts / 5.5 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600/800 Rush, Switchback, Voyageur, RMK	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	8–10 oz / 237–296 mL	—	refer to service manual for proper filling	4 – 6.3 quarts / 3.8 – 6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2015

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
550 Indy	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Voyager	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Widetrak	capacity	2.0 quarts / 1.9 liters Polaris Blue Synthetic Blend 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
600 Indy	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	—
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Widetrak	capacity	3.0 quarts / 2.8 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	—
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 Racer	capacity	3.0 quarts / 2.8 liters VES Extreme Synthetic 2-Cycle Oil	11 oz / 325 mL	—	refer to service manual for proper filling	—
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600/800 Rush, Switchback, Voyager, RMK	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	8–10 oz / 237–296 mL	—	refer to service manual for proper filling	—
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2014

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz(.6L) dry engine *Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
550 Indy	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
550 Voyageur	capacity	3.0 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
EDGE / Widetrak	capacity	2.0 quarts / 1.9 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 Indy	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Turbo IQ LXT	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	7.8 quarts / 7.4 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Widetrak	capacity	3.0 quarts / 2.8 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	9.8 quarts / 9.3 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Racer	capacity	3.0 quarts / 2.8 liters VES Extreme Synthetic 2-Cycle Oil	9 oz. / 266.2 mL	—	refer to service manual for proper filling	5.7 quarts / 5.4 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600/800 Rush, Switchback, Voyageur, RMK	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	8–10 oz / 237–296 mL	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2013

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz.(6L) dry engine *Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
EDGE / Widetrak	capacity	2.0 quarts / 1.9 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Turbo IQ LXT	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	7.8 quarts / 7.4 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
FS IQ Widetrak	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	20 oz / 592 mL	—	refer to service manual for proper filling	8.9 quarts / 8.4 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
550 IQ LXT / Shift / Shift 136	capacity	3 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	11 oz / 325 mL	—	refer to service manual for proper filling	N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
600 IQ LXT	capacity	3.4 quarts / 3.2 liters VES Synthetic 2-Cycle Oil	11 oz / 325 mL	—	refer to service manual for proper filling	7 quarts / 6.6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Widetrak	capacity	3.0 quarts / 2.8 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	9.8 quarts / 9.3 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Racer	capacity	3.0 quarts / 2.8 liters VES Extreme Synthetic 2-Cycle Oil	11 oz. / 325.3 mL	—	refer to service manual for proper filling	5.3 quarts / 5 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600/800 Rush, Switchback, Voyager, RMK	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	8-10 oz / 237-296 mL	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2012

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz.(6L) dry engine *Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
EDGE / Widetrak	capacity	2.0 quarts / 1.9 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 Indy	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Turbo IQ / IQ LXT / LX	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	7.8 quarts / 7.4 liters LX: 9.6 quarts / 9.1 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
FS IQ Widetrak	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	20 oz / 592 mL	—	refer to service manual for proper filling	8.9 quarts / 8.4 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
550 IQ LXT / Shift / Shift 136	capacity	3 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	11 oz / 325 mL	—	refer to service manual for proper filling	N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
600 IQ LXT	capacity	3.4 quarts / 3.2 liters VES Synthetic 2-Cycle Oil	11 oz / 325 mL	—	refer to service manual for proper filling	7 quarts / 6.6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Widetrak	capacity	3.0 quarts / 2.8 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	9.8 quarts / 9.3 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Racer	capacity	3.0 quarts / 2.8 liters VES Extreme Synthetic 2-Cycle Oil	11 oz. / 325.3 mL	—	refer to service manual for proper filling	5.3 quarts / 5 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600/800 Rush, Switchback, Voyageur, RMK	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	8–10 oz / 237–296 mL	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2011

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz.(6L) dry engine *Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
EDGE / Widetrak	capacity	2.0 quarts / 1.9 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Turbo IQ / IQ LXT / LX	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	7.8 quarts / 7.4 liters LX: 9.6 quarts / 9.1 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
FS IQ Widetrak	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	20 oz / 592 mL	—	refer to service manual for proper filling	8.9 quarts / 8.4 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
550 IQ LXT / Shift / Shift 136	capacity	3 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	11 oz / 325 mL	—	refer to service manual for proper filling	N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
600 IQ LXT	capacity	3.4 quarts / 3.2 liters VES Synthetic 2-Cycle Oil	11 oz / 325 mL	—	refer to service manual for proper filling	7 quarts / 6.6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Widetrak	capacity	3.0 quarts / 2.8 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	9.8 quarts / 9.3 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Racer	capacity	3.0 quarts / 2.8 liters VES Extreme Synthetic 2-Cycle Oil	11 oz. / 325.3 mL	—	refer to service manual for proper filling	5.3 quarts / 5 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600/800 Rush, Switchback, Voyageur, RMK	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	8–10 oz / 237–296 mL	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2010

MODEL		2-CYCLE OIL *OIL TYPE WILL VARY BY MODEL	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz.(6L) dry engine *Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
Widetrak LX	capacity	2.0 quarts / 1.9 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Trail RMK / Touring	capacity	3.4 quarts / 3.2 liters VES Synthetic 2-Cycle Oil	9 oz / 266 mL	—	refer to service manual for proper filling	N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
FST IQ Touring/ IQ Turbo LX/ Dragon	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	7.8 quarts / 7.4 liters LX: 9.6 quarts / 9.1 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
FS IQ Widetrak	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	20 oz / 592 mL	—	refer to service manual for proper filling	8.9 quarts / 8.4 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
550 IQ Shift	capacity	3 quarts / 2.8 liters Polaris Blue Synthetic Blend 2-Cycle Oil	11 oz / 325 mL	—	refer to service manual for proper filling	N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
600 IQ LX	capacity	3.4 quarts / 3.2 liters VES Synthetic 2-Cycle Oil	11 oz / 325 mL	—	refer to service manual for proper filling	8.5 quarts / 8 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Widetrak	capacity	3.0 quarts / 2.8 liters VES Synthetic 2-Cycle Oil	20 oz / 592 mL	—	refer to service manual for proper filling	9.8 quarts / 9.3 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Racer	capacity	3.0 quarts / 2.8 liters VES Extreme Synthetic 2-Cycle Oil	11 oz. / 325.3 mL	—	refer to service manual for proper filling	5.3 quarts / 5 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 /800 Rush, Switchback, RMK, Dragon	capacity	3.8 quarts / 3.6 liters VES Synthetic 2-Cycle Oil	8–10 oz / 237–296 mL	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2009

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz.(6L) dry engine *Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
Widetrak LX	capacity	2.0 quarts / 1.9 liters	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Trail RMK / Touring / 550 Transport	capacity	3.4 quarts / 3.2 liters	9 oz / 266 mL	—	refer to service manual for proper filling	N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	
FST IQ Touring/ IQ Turbo LX/ Dragon / Switchback	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	6 – 7 quarts / 6 – 6.6 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
FS IQ Widetrak	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	20 oz / 592 mL	—	refer to service manual for proper filling	8.9 quarts / 8.4 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
550/ 600 IQ Shift	capacity	3 quarts / 2.8 liters	11 oz / 325 mL	—	refer to service manual for proper filling	550 : N / A 600: 8.5 quarts / 8 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ RR	capacity	2.5 quarts / 2.4 liters	9 oz. / 266 mL	—	refer to service manual for proper filling	10.1 quarts / 9.6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Racer	capacity	3.0 quarts / 2.8 liters	11 oz. / 325.3 mL	—	refer to service manual for proper filling	5.3 quarts / 5 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 /800 Rush, Switchback, RMK, Dragon	capacity	3.4 – 3.8 quarts / 3.2 – 3.6 liters	8–10 oz / 237–296 mL	—	refer to service manual for proper filling	5 quarts / 4.7 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2008

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz.(6L) dry engine *Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
Widetrak LX	capacity	2.0 quarts / 1.9 liters	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Trail / 550 LX / 340	capacity	3.4 quarts / 3.2 liters	9 oz / 266 mL	—	refer to service manual for proper filling	N / A 340 : 6.3 quarts / 6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
FS IQ Widetrak	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	6 – 7 quarts / 6 – 6.6 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
FST / IQ Turbo / Turbo	capacity	FST: 3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	6 – 7 quarts / 6 – 6.6 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 RR	capacity	2.5 quarts / 2.4 liters	9 oz. / 266 mL	—	refer to service manual for proper filling	10.1 quarts / 9.6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 IQ Racer	capacity	3.0 quarts / 2.8 liters	11 oz. / 325.3 mL	—	refer to service manual for proper filling	5.3 quarts / 5 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
IQ Shift / 600 / 700 / 800 Rush, Switchback, RMK, Dragon	capacity	3.0 – 3.8 quarts / 2.8 – 3.6 liters	8–10 oz / 237–296 mL	—	refer to service manual for proper filling	5 – 9 quarts / 4.7 – 8.5 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2007

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz.(6L) dry engine Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
Widetrak LX	capacity	2.0 quarts / 1.9 liters	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Trail / 340 / 500 / 550	capacity	3.4 quarts / 3.2 liters	9 oz / 266 mL	—	refer to service manual for proper filling	N / A 340 : 6.3 quarts / 6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
FS IQ Widetrak	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	6– 7 quarts / 6 – 6.6 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
FST Classic / Touring / IQ	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	6– 7 quarts / 6 – 6.6 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
440 Racer	capacity	N / A	9 oz. / 266 mL	—	refer to service manual for proper filling	4 quarts / 3.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 / 700 Switchback / RMK / Dragon	capacity	3.0 – 3.8 quarts / 2.8 – 3.6 liters	8–10 oz / 237–296 mL	—	refer to service manual for proper filling	5 – 9 quarts / 4.7 – 8.5 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2006

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882 *UNLESS OTHERWISE STATED	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
Indy 120	capacity	20 oz.(6L) dry engine *Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
Widetrak LX	capacity	2.0 quarts / 1.9 liters	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Trail / 340 / 500 / 550	capacity	3.4 quarts / 3.2 liters	9 oz / 266 mL	—	refer to service manual for proper filling	N / A 340 : 6.3 quarts / 6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
FS Classic / Touring	capacity	2.5 quarts / 2.3 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	6– 7 quarts / 6 – 6.6 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
FST Classic / Touring / Switchback	capacity	3 quarts / 2.8 liters *Polaris PS-4	9 oz / 266 mL	—	refer to service manual for proper filling	6– 7 quarts / 6 – 6.6 liters
	interval	1500 miles / 2400 km	500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
440 Racer	capacity	N / A	9 oz. / 266 mL	—	refer to service manual for proper filling	4 quarts / 3.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
600 / 700 Classic, Dragon	capacity	3.0 – 3.8 quarts / 2.8 – 3.6 liters	8–10 oz / 237–296 mL	—	refer to service manual for proper filling	5 – 9 quarts / 4.7 – 8.5 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2005

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
120 XC SP / PRO X	capacity	20 oz(.6L) dry engine Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
Trail Sport: 500 Indy, Supersport	capacity	3.25 quarts / 3 liters	9 oz / 266 mL	—	refer to service manual for proper filling	5 quarts / 4.7 liters Supersport : N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Touring: 340 Edge, Trail / DLX, 600 Edge, 800 Edge	capacity	3.2 quarts / 3 liters	9 oz / 266 mL	—	refer to service manual for proper filling	600, 800: 5.8 quarts / 5.5 liters 340, Trail / DLX: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Widetrak LX	capacity	2.0 quarts / 1.9 liters	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Frontier Touring	capacity	2 quarts / 1.9 liters	13 oz / 384.5 mL	—	refer to service manual for proper filling	5.5 quarts / 5.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Classic: 340, 500, 550, 600	capacity	3.25 quarts / 3 liters	9 oz / 266 mL	—	refer to service manual for proper filling	600 : 5.9 quarts / 5.6 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Deep Snow: Trail RMK, 600 / 700 / 800 RMK, 600 / 800 Switchback, 900 RMK	capacity	3.25 quarts / 3 liters	9 — 11 oz / 266 — 325 mL	—	refer to service manual for proper filling	5 — 6.9 quarts / 4.7 — 6.4 liters Trail RMK: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Performance: 500 / 600 / 700 / 800 XC SP, 900 Fusion	capacity	3 — 3.25 quarts / 2.8 — 3.1 liters	9 — 11 oz / 266 — 325 mL	—	refer to service manual for proper filling	5.2 — 6.7 quarts / 4.9 — 6.3 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2004

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
120 XC SP / PRO X	capacity	20 oz(.6L) dry engine Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
Trail Sport: 340 Edge, 500 Edge, Super Sport	capacity	3.25 quarts / 3 liters	500: 12 oz / 355 mL 9 oz / 266 mL	—	refer to service manual for proper filling	500: 5 quarts / 4.7 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Touring: 340, Sport, Trail , 600 / 700 / 800 Classic	capacity	3.2 quarts / 3 liters	11 oz / 325 mL	—	refer to service manual for proper filling	600, 700, 800: 5.8 quarts / 5.5 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Widetrak LX	capacity	2.0 quarts / 1.9 liters	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Frontier: Touring, Classic	capacity	2 quarts / 1.9 liters	13 oz / 384.5 mL	—	refer to service manual for proper filling	5.5 quarts / 5.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Trail Luxury: 340 Edge, 500, 550, 600, 700, 800	capacity	3.25 quarts / 3 liters	9 oz / 266 mL	—	refer to service manual for proper filling	600, 700, 800: 5.9 quarts / 5.6 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Deep Snow: Trail RMK, 600 / 700 / 800 RMK, 600 / 700 / 800 Switchback	capacity	3.25 quarts / 3 liters	11 oz / 325 mL	—	refer to service manual for proper filling	4.3 quarts / 4.1 liters Trail RMK: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Pro: 440 / 550 / 600 / 700 / 800 X, 800 XR	capacity	3.25 quarts / 3 liters 440: N / A	9 oz / 266 mL 440: N / A	—	refer to service manual for proper filling	4.5 quarts / 4.2 liters 440, 550 : N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Performance: 500 / 600 / 700 / 800 XC SP	capacity	3.25 quarts / 3 liters	9 oz / 266 mL	—	refer to service manual for proper filling	5.9 quarts / 5.6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2003

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
120 XC SP / PRO X	capacity	20 oz.(6L) dry engine Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
Trail Sport: 340 Edge, 340 Classic, 500 Edge, Super Sport, 440 PRO X FAN	capacity	3.25 — 4 quarts / 3 — 3.8 liters	500, Super Sport: 11 oz / 325 mL 9 oz / 266 mL	—	refer to service manual for proper filling	500: 4 quarts / 3.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Touring: 340, Sport, Trail, 500 / 600 / 700 / 800 Classic	capacity	2 – 4 quarts / 1.9 — 3.8 liters	9 – 13 oz / 266 – 384 mL	—	refer to service manual for proper filling	600, 500, 700: 3.8 – 5.8 quarts / 3.6 – 5.5 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Widetrak LX	capacity	2.0 quarts / 1.9 liters	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Frontier: Touring, Classic	capacity	2 quarts / 1.9 liters	12 oz / 325 mL	—	refer to service manual for proper filling	6 quarts / 5.6 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Trail Luxury: 340 Edge, 500, 550, 600, 700, 800	capacity	3.25 quarts / 3 liters	11 oz / 325 mL	—	refer to service manual for proper filling	500, 600, 700, 800: 4 quarts / 3.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Deep Snow: Trail RMK, 600 / 700 / 800 RMK, 700 / 800 SKS	capacity	3 — 4 quarts / 2.8 — 3.8 liters	9 – 11 oz / 266– 325 mL	—	refer to service manual for proper filling	4.7 quarts / 4.5 liters Trail RMK: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
High Performance: 440 PRO X FAN, 440 / 600 / 700 / 800 PRO X	capacity	3.25 quarts / 3 liters 440 PRO X: N / A	9 – 11 oz / 266 – 325 mL 440: N / A	—	refer to service manual for proper filling	4.5 quarts / 4.2 liters 440 PRO X FAN: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Performance: 500 / 600 / 700 / 800 XC SP, 800 XCR	capacity	3.25 quarts / 3 liters 800 XCR: 2.4 quarts / 2.3 liters	11 oz / 325 mL 800 XCR: 9 oz / 266 mL	—	refer to service manual for proper filling	4.7 quarts / 4.5 liters 800 XCR: 7.3 quarts / 6.9 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2002

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
120 XC SP / PRO X	capacity	20 oz.(6L) dry engine Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
Trail Sport: 340 Deluxe, Indy 500, Super Sport	capacity	3.25 — 4 quarts / 3 — 3.8 liters	500, Super Sport: 11 oz / 325 mL 9 oz / 266 mL	—	refer to service manual for proper filling	500: 4 quarts / 3.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Two-Up / Touring: 340, Sport, Trail , 500 / 600 Classic	capacity	2 — 4 quarts / 1.9 — 3.8 liters	9 — 13 oz / 266 — 384 mL	—	refer to service manual for proper filling	600, 500: 3.8 — 5.8 quarts / 3.6 — 5.5 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Widetrak LX	capacity	2.0 quarts / 1.9 liters	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Frontier	capacity	2 quarts / 1.9 liters	9 oz / 265 mL	—	refer to service manual for proper filling	3.2 quarts / 3 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Trail Luxury: 500, 550, 600, 700	capacity	4 quarts / 3.8 liters	13 oz / 384 mL	—	refer to service manual for proper filling	4 quarts / 3.8 liters 550: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Deep Snow: Trail RMK, 500/ 700 SKS, 500 RMK, 600 / 700 / 800 RMK Edge	capacity	3 — 4 quarts / 2.8 — 3.8 liters	9 — 11 oz / 266 — 325 mL	—	refer to service manual for proper filling	4.3 — 6 quarts / 4 — 5.7 liters Trail RMK: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
High Performance: 440 PRO X FAN, 440 / 600 PRO X	capacity	3.5 quarts / 3.3 liters 440 PRO X: N / A	9 — 11 oz / 266 — 325 mL 440: N / A	—	refer to service manual for proper filling	4.5 quarts / 4.2 liters 440 PRO X FAN: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Performance: 500 XC, 500 / 600 / 700 / 800 XC SP, 800 XCR	capacity	4 quarts / 3.8 liters 800 XCR: 2.4 quarts / 2.3 liters	11 oz / 325 mL 800 XCR: 9 oz / 266 mL	—	refer to service manual for proper filling	4 quarts / 3.8 liters 800 XCR: 7.3 quarts / 6.9 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2001

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
120 XC SP / PRO X	capacity	20 oz.(6L) dry engine Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
Trail Sport: 340 Deluxe, Indy 500, Super Sport Edge	capacity	2 — 4 quarts / 1.9 — 3.8 liters	500, Super Sport: 11 oz / 325 mL 9 oz / 266 mL	—	refer to service manual for proper filling	500: 4 quarts / 3.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Two-Up / Touring: 340, Sport / ES, Trail , 500 / 600 Classic	capacity	2 – 3 quarts / 1.9 — 2.8 liters	9 oz / 266 mL	—	refer to service manual for proper filling	600, 500: 3 quarts / 2.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Widetrak LX	capacity	2.0 quarts / 1.9 liters	20 oz / 592 mL	—	refer to service manual for proper filling	3.4 quarts / 3.2 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Trail Luxury: 500, 600, 700, 800 LE	capacity	4 quarts / 3.8 liters	13 oz / 384 mL	—	refer to service manual for proper filling	4 quarts / 3.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Deep Snow: Trail RMK, 700 SKS, 500 / 600 / 700 / 800 RMK, 800 RMK Snow-check Special	capacity	3 quarts / 2.8 liters	9 – 11 oz / 266– 325 mL	—	refer to service manual for proper filling	5.5 quarts / 5.2 liters Trail RMK: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
High Performance: 440 XCF SP, 440 / 600 Edge Pro X	capacity	3.5 quarts / 3.3 liters	9 oz / 266 mL	—	refer to service manual for proper filling	4.5 quarts / 4.2 liters 440 XCF SP: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Performance: 500 XC, 500 / 600 / 700 / 800 XC SP, 600 EDGE X, 800 XCR	capacity	4 quarts / 3.8 liters 800 XCR: 2.4 quarts / 2.3 liters	11 oz / 325 mL 800 XCR: 9 oz / 266 mL	—	refer to service manual for proper filling	4 quarts / 3.8 liters 800 XCR: 7.3 quarts / 6.9 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

SNOWMOBILE LUBE CHART 2000

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
120 XC SP / PRO X	capacity	20 oz (.6L) dry engine Polaris PS-4	—	—	N/A	N/A
	interval	50 hour	—	—		
Trail Sport: 340 Deluxe, Indy 500, Super Sport	capacity	2 — 3 quarts / 1.9 — 2.8 liters	500, Super Sport: 7 oz / 210 mL 9 oz / 266 mL	—	refer to service manual for proper filling	500: 3 quarts / 2.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Two-Up / Touring: 340, Sport / ES, Trail, 500 Classic, 600, Classic, Triumph	capacity	2 — 3 quarts / 1.9 — 2.8 liters	9 oz / 266 mL Triumph: 7 oz / 210 mL	—	refer to service manual for proper filling	Classic, Triumph, 600, 500: 3 quarts / 2.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Widetrak LX	capacity	2.4 quarts / 2.3 liters	20 oz / 592 mL	—	refer to service manual for proper filling	3 quarts / 2.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Deep Snow: Trail RMK, 700 SKS, 500 / 600 / 700 / 800 RMK	capacity	3 quarts / 2.8 liters	7 oz / 210 mL	—	refer to service manual for proper filling	5.5 quarts / 5.2 liters Trail RMK: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
High Performance: 440 XC SP, 440 / 600 Edge Pro X	capacity	3.5 quarts / 3.3 liters	9 oz / 266 mL	—	refer to service manual for proper filling	4 quarts / 3.8 liters 440 XCF SP: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Performance: 500 XC, 500 / 600 / 700 XC SP, 800 XCR, 600 / 700 XC DLX	capacity	3 quarts / 2.8 liters 800 XCR: 2.4 quarts / 2.3 liters	7 oz / 210 mL 600 / 700 XC DLX: 9 oz / 266 mL	—	refer to service manual for proper filling	3 quarts / 2.8 liters 800 XCR: 7.3 quarts / 6.9 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

3

SNOWMOBILE LUBE CHART 1999

MODEL		VES SYNTHETIC 2-CYCLE OIL 2877882	CHAINCASE OIL 2873105	BRAKE FLUID 2872189	REBUILDABLE SHOCK OIL SHOCK OIL	ANTIFREEZE 50/50 EXTENDED LIFE ANTI-FREEZE
340 Deluxe, Indy Sport, Trail, Super Sport, Indy 500, Indy RMK	capacity	2 quarts / 1.9 liters Super Sport: 3 quarts / 2.8 liters	7 oz / 210 mL	—	refer to service manual for proper filling	RMK, 500: 3 quarts / 2.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
340, Indy Sport Touring, Indy Transport, Trail Touring, 500 Classic, Classic Touring, XLT Special, XLT Classic, XLT Touring	capacity	2 quarts / 1.9 liters	7 oz / 210 mL XLT Touring, XLT Classic, Classic Touring, 500, Trail, Transport: 9 oz / 266 mL	—	refer to service manual for proper filling	XLT Touring, XLT Classic, XLT Special, Classic Touring, 500: 3 quarts / 2.8 liters N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Widetrak LX	capacity	2.4 quarts / 2.3 liters	20 oz / 592 mL	—	refer to service manual for proper filling	3 quarts / 2.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Trail RMK, Indy 600 / 700 RMK, Indy 700 SKS	capacity	3 quarts / 2.8 liters	7 oz / 210 mL	—	refer to service manual for proper filling	3 quarts / 2.8 liters Trail RMK: N / A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
Indy 700/ 800 XCR	capacity	2.4 quarts / 2.3 liters	7 oz / 210 mL	—	refer to service manual for proper filling	3 quarts / 2.8 liters
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years
XCF, 440 XCR, Indy 500 / 600 / 700 XC / SP	capacity	3 quarts / 2.8 liters	7 oz / 210 mL	—	refer to service manual for proper filling	3 quarts / 2.8 liters XCF: N/A
	interval		500 mile break in, 1500 miles (2400 km)	2000 miles (3200 km)	High performance shocks should have oil changed and recharged at the end of every riding season.	5 years

