

# LINE OUT HARNESS KIT



**P/N 2881652**

## APPLICATION

All RZR Models

## FUNCTION

Transfers audio signal from source unit

## COMPATIBILITY

Compatible Harnesses:

- Polaris Interactive Digital Display Adapter Harness (PN 2881649)
- Y-Harness (PN 2881651)
- Line Out Harness (PN 2881652)
- MTX® Audio Adapter Harness (PN 2881648)

Compatible Audio Devices:

- Polaris Interactive Digital Display (PN 2881554); also requires Polaris Interactive Digital Display Adapter Harness (PN 2881649)
- Bluetooth® Controller (PN 2881470)
- Extreme Audio Pods (PN 2881227)
- 4 Speaker Sound Bar (PN 2881230)
- 8 Speaker Sound Bar (PN 2881465)
- MTX® Overhead Audio Pod (PN 2879459); also requires MTX® Audio Adapter Harness (PN 2881648)
- MTX® Rear Two Speaker Add-On (PN 2879514); also requires MTX® Audio Adapter Harness (PN 2881648)

## BEFORE YOU BEGIN

Read these instructions and check to be sure all parts and tools are accounted for. Please retain these installation instructions for future reference and parts ordering information.

## KIT CONTENTS

This Kit includes:

REF	QTY	PART DESCRIPTION	PART NUMBER
1	1	Audio Harness, Line Out	2413384
		Instructions	9926774

## TOOLS REQUIRED

None

## IMPORTANT

Your LINE OUT HARNESS KIT is exclusively designed for your vehicle. Please read the installation instructions thoroughly before beginning. Installation is easier if the vehicle is clean and free of debris. For your safety, and to ensure a satisfactory installation, perform all installation steps correctly in the sequence shown.

## ASSEMBLY TIME

Approximately 15 minutes

## INSTALLATION INSTRUCTIONS

**If harness is used with Polaris Interactive Digital Display (PN 2881554) or Bluetooth® Controller (PN 2881470):**

1. Route female 4–pin connector into hole at top of driver side A-pillar, down ROPS, out of welded coupler at base of pillar, through slot in lower left front fender, along frame tubing, and through firewall grommet (below terminal block).
2. Connect female 4–pin connector to Polaris Interactive Digital Display Adapter Harness (PN 2881649) or Bluetooth® Controller (PN 2881470).

### NOTE

For Bluetooth® Controller: Line out harness must be connected to Y-Harness (PN 2881651, sold separately), then Y-Harness is connected to Bluetooth® Controller.

**If harness is used with overhead source unit:**

1. Connect female 4–pin connector to source unit (or Y-Harness (PN 2881651) if subwoofer is installed).
2. Route male 4–pin connector from top of driver side A-pillar, along ROPS, to driver side B-pillar, across rear cross member to passenger side B-pillar. Secure as required.
3. Connect male 4–pin connector to audio device or Y-Harness (PN 2881651).