

Prepared according to Global Harmonized System (GHS) standards

SECTION 1

CHEMICAL PRODUCT IDENTIFICATION

Polaris Sales Inc. 2100 Highway 55 Medina, MN 55340 Tel: 763-542-0500

Product Trade Name:

Brutus Angle Broom Oil

CAS Number: Synonyms/Other: Part Number(s): Recommended Use: Restrictions on Use: Created Date: Preparation/Revision Date: Emergency Phone Number: SDS CODE: Mixture N/A N/A Hydraulic Fluid Not Determined 5/30/2015 5/30/2015 1-800-424-9300 (CHEMTREC) 12010

SECTION 2

HAZARD IDENTIFICATION

Appearance:	Clear, Amber
Odor:	Petroleum
Classification:	This material is not considered to be hazardous according to the Globally Harmonized System of Classification and Labelling Chemicals (GHS), Third Revised Edition.
Target Organs:	Not applicable.
Pictogram(s):	None required.
Signal Word:	None required.
Hazard Statement:	Not required.
Other Hazards:	Not determined.
Prevention:	None required.
Response:	None required.
Storage Procedures:	None required.
Disposal:	None required.
Other:	See section 11 for complete health hazard information.

SECTION 3

COMPOSITION OF INGREDIENTS

No Hazardous Substance(s) or Complex Substance(s) Required for Disclosure.

The balance of components do not contribute to the overall classification of the fluid, according to the GHS Standard.

SECTION 4	FIRST AID MEASURES
Eye Contact:	If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.
Skin Contact:	Call a doctor if you feel unwell.
Inhalation:	Get medical advice or attention if you feel unwell or are concerned.
Ingestion:	If you feel unwell or concerned: Get medical advice/attention. Rinse mouth. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.
Other:	No additional information



SECTION 5

FIRE FIGHTING MEASURES

Flash Point: Flammable limits: Extinguishing media: Special firefighting procedures	 265°C by Cleveland Open Cup Tester. Not determined. Use dry chemical, alcohol foam, all purpose AFFF or carbon dioxide to extinguish fire. DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).
Unusual fire & explosion hazards:	Dense smoke may be generated while burning. Toxic fumes, gases or vapors may evolve on burning. High temperatures may create heavy flammable vapors that may settle along ground level and low spots to create an invisible fire hazard.
Byproducts of combustion:	Fires involving this product may release oxides of carbon, phosphorus, nitrogen and sulfur; reactive hydrocarbons and irritating vapors.
Autoignition temperature:	Not determined.
Explosion data:	Not determined. Care should always be exercised in dust/mist areas.
Other:	Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Spill control procedures (land):	Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spill, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. If a large spill occurs notify appropriate authorities. In case of road spill or accident contact Chem-Trec (800-424-9300).
Spill control procedures (water):	Try to contain large spills with floating booms to prevent spill from spreading. Remove from surface by skimming or with suitable adsorbents. If a large spill occurs notify appropriate authorities (normally the National Response Center or Coast Guard at 800-424-8802).
Waste disposal method:	Do not empty into drains. All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.
Other:	CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will be regulated.
SECTION 7	HANDLING AND STORAGE
Handling procedures:	Keep containers closed when not in use. Do not transfer to unmarked containers. Empty

res: Keep containers closed when not in use. Do not transfer to unmarked containers. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Handling temperatures should not exceed 60° (140°F) to min imize danger of burns. Open containers carefully in a well ventilated area or use appropriate respiratory protection. Wash thoroughly after handling.



Storage procedures:

Store containers away from heat, sparks, open flame, or oxidizing materials. Extended storage at excessive temperatures may produce odorous and toxic fumes from product decomposition.

Additional information:

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits/standards for materials that can be formed when handling this product:

No additional information.

		OSHA TWA	OSHA STEL	ACGIH TWA
Contains highly refined petroleum oil		*5 mg/m³ (PEL)	*10 mg/m ³	*5 mg/m³ (TLV)
	* Exposure limits not defined	d. Limits used a	re for, "oil mist".	
	TWA – Time Weighted Aver any 8-hour work shift of a 40 STEL – Short Term Exposur average exposure which sha unless another time limit is s	-hour work week e Limit is the em all not be exceed	which shall not be ployee's 15-minute	e exceeded. e time weighted
	All base oils, including additi	ve carriers, cont	ain <3.0% DMSO (extractable material.
Personal protection:	Applicable mainly to persons service/maintenance, and cle	•		ch as packaging of product,
Respiratory protection:	None required if ventilation meeting OSHA 1910.134 an may occur, wear an MSHA/I purifying respirator.	n is adequate. d ANSI Z88.2 re	Otherwise a resp quirements must b	e followed. Where misting
Eye protection:	Eye protection is strongly vented/splash proof goggles			
Hand protection:	Impervious, chemically resis sensitization and absorption.	stant gloves sucl		
Other protection:	Use of an apron and overbod nitrile rubber is recommend material use insulated protect contaminated leather articles	ed based on lev ctive equipment.	vel of activity and Launder soiled cl	exposure. If handling hot othes. Properly dispose of
Local control measures:	Use adequate ventilation where methods such as fume hood areas. If vapor or mist is graccordance with good engine below the specified exposure areas where this material is the specified structure.	ds or area fans enerated when t neering practice ire. Eyewash si	may be used to r the material handl must be provided tations and showe	educe localized vapor/mist ed, adequate ventilation in to maintain concentrations
Other:	Consumption of food and dri Always wash hands and face			

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Odor: Odor threshold: pH: Clear, Amber Petroleum Not determined. Not applicable.



Melting/Freezing point:	Not determined.
Initial boiling point:	Not determined.
Boiling range:	Not determined.
Flash point:	265°C.
Evaporation rate:	Not determined.
Flammability:	Not determined.
Upper flammable limit:	Not determined.
Lower flammable limit:	Not determined.
Vapor pressure:	Not determined.
Vapor density:	Not determined.
Relative density:	1.076 @ 15.6℃
Solubility:	Negligible in water, miscible in most petroleum solvents.
Partition Coefficient:	Not determined.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Viscosity:	460 cSt at 40℃.
Other	Not applicable.

SECTION 10

STABILITY AND REACTIVITY

Reactivity	
Chemical stability:	Material is chemically stable at room temperatures and pressure.
Hazardous polymerization:	Will not occur.
Conditions to avoid:	Avoid high temperatures and product contamination.
Incompatibility with other materials:	Avoid contact with acids and strong oxidizing materials.
Decomposition products:	Smoke, carbon monoxide, carbon dioxide, and other aldehydes of incomplete combustion. Oxides of carbon, nitrogen, and sulfur; reactive hydrocarbons and irritating vapors.
Other:	Not applicable.

SECTION 11

TOXICOLOGICAL INFORMATION

Acute toxicity (LD50) *See note at the bottom of the section

Oral:	>5000 mg/kg
Dermal:	>5000 mg/kg
Inhalation:	>20.0 mg/l
Skin irritation:	Non-irritant
Eye irritation:	Non-irritant
Dermal sensitization:	Not expected to have a sensitizing effect.
Respiratory sensitization:	Not expected to have a sensitizing effect.
Aspiration Hazard:	Not applicable
Chronic Toxicity	
Mutagenicity:	Not suspected of causing genetic defects
Carcinogenicity:	Not suspected of causing cancer.
Reproductive toxicity:	Not expected to have adverse effects.
STOT-single exposure:	Not expected to have adverse effects.
STOT-repeated exposure:	Not expected to have long term adverse effects.
Other:	*All data in this section is based off calculations from Part 3 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.



SECTION 12

ECOLOGICAL INFORMATION

Environmental toxicity	
Fish:	> 100 mg/l.
Invertebrates:	> 100 mg/l.
Aquatic plants:	> 100 mg/l.
Microorganism:	> 100 mg/l.
Persistence/Degradability:	This product is not expected to be readily biodegradable.
Bioaccumulation:	Not determined.
Mobility in soil:	Not determined.
Other:	All classifications are based on calculations in Part 4 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

SECTION 13	DISPOSAL CONSIDERATIONS
Waste disposal:	This product unadulterated by other materials can be classified as a non-hazardous waste. Depending on use, used product may be regulated. Dispose of in a licensed facility. Do not discharge product in to sewer system. Dispose of containers by crushing or puncturing, so as to prevent unauthorized use of used containers. Waste management should be in full compliance with federal, state, and local laws.
Other	The transportation, storage, treatment and disposal of RCRA waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.

SECTION 14	TRANSPORT INFORMATION
Land Transport (DOT):	Not Regulated.
Proper Shipping Name:	Not Applicable.
Land Transport (TDG):	Not Regulated.
Proper Shipping Name:	Not Applicable.
Sea Transport (IMDG):	Not Regulated.
Proper Shipping Name:	Not Applicable.
Air Transport (IATA):	Not Regulated.
Proper Shipping Name:	Not Applicable.
Other:	Not Applicable.
SECTION 15	REGULATORY INFORMATION

Federal Regulation Clean water act/oil:

Under Section 311 of the Clean Water Act (40 CFR 110) and the Oil Pollution Control Act of 1990, this material is considered an oil. Any spill or discharges that produce a visible sheen or film on surface of water, or in waterways, ditches, or sewers leading to surface water must be reported. Contact the National Response Center at 800-424-8802. All components of this material are listed in the U.S. TSCA Inventory. Not applicable.

TSCA: Other TSCA:

ENGINEERED LUBRICANTS			Revision Date: 5	50/15		
SARA title III:	Section 302/304 extremely haz	zardous substances:				
	None.					
	Section 311, 312 hazard categ	orization:				
	Acute (immediate hea	alth effects):	NO			
	Chronic (delayed hea	Ith effects):	NO			
	Fire (hazard):		NO			
	Reactivity (hazard):		NO			
	Pressure (sudden re	lease hazard):	NO			
	Section 313 toxic chemicals:	Section 313 toxic chemicals:				
	No components present are at or greater than the de minimis (minimum reportable) concentration requirements for reporting.					
CERCLA:	For stationary/moving sources – reportable quantity (due to): Not hazardous due to the petroleum exclusion.					
State Regulations						
Right-to-know	Not determined.					
Other:	Environmental Response Con may be reportable to the Nation	npensation and Liabili on Response Center (n reporting under the Compreh by Act (CERCLA). However, re under the Clean Water Act, 33 ire to report may result in subs	leases U.S.C.		
	Recommend contacting the lo local reporting requirements an		event of any type of spill to dete eanup.	ermine		
SECTION 16	OTHER IN	FORMATION				
	NFPA 704	NPCA-HMIS	KEY			
HEALTH:	1	1	0 = Minimal			
FIRE:	1	1	1 = Slight			
	0	0				

FIRE:	1	1	1 = Slight
REACTIVITY:	0	0	2 = Moderate
SPECIFIC HAZARD:	None	N/A	3 = Serious
PROTECTION INDEX:	N/A	В	4 = Severe

Version: I

POLARIS

INFORMATION PROVIDED IN THIS SDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF THE AUTHORS' KNOWLEDGE. HOWEVER, THE AUTHOR'S MAKE NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. THE AUTHORS ASSUME NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Revisions / Comments:

None.